

MOTOR FINISH



BLADE FINISHES

Walnut, Satin Black



AIR PERFORMANCE

AIRFLOW Cubic Ft. Per Minute on High	RPM Revolutions Per Minute on High	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt
4479	153	48	93

CFM (Low)	1795
RPM (Low)	65
Watts (Low)	14

SPECIFICATIONS

Light Source			
Downlight Included	Yes	Downlight Option	Removable
Watts (High)	48	Watts (Low)	14
Dimmable	Yes	Lamp Included	Included
Lamp Type	B10	Light Source	LED
# of Bulbs/LED Modules	3	Optional Light Kit Available	Removable
Socket Type	E12 Candelabra		
Photometrics			
Color Rendering Index	90	Delivered Efficacy (Lumens/Watt)	75
Kelvin Temperature	2700K		
Electrical			
Amps (High)	0.40	Amps (Low)	0.20
Motor Size	153MM X 20MM	Motor Type	AC Induction
Supply Wire (Degrees)	90		
Dimensions			
Downrod 1	1.00" OD X 4.50"	Downrod 1 - Measurement A	18.50"
Downrod 1 - Measurement B	9.00"	Downrod 1 - Measurement C	8.75"
Base Backplate	6.00 DIA	Weight	23.80 LBS
Mounting/Installation			
Minimum Distance from Fan to Floor	7.0 feet	Interior/Exterior	Exterior
Lead Wire Length	78"	Location Rating	Damp
Mounting Style	Downrod	Mounting Weight	21.30 LBS

FIXTURE ATTRIBUTES

Product/Ordering Information			
SKU	310073DBK	Finish	Distressed Black
Style	Coastal	UPC	783927001021

Housing

Fan Primary Control System	65K Cooltouch - Full Function	Remote Included	Yes
Diffuser Description	Clear Seeded	Primary Material	STEEL
Max Stem Tilt	22.00		

Blade Finish & Specs

Blade Finish 1	Walnut	Blade Finish 2	Satin Black
Blade Material	ABS	Blade Pitch	12
Blade Sweep	52	Blades Included	Yes
Blades Reversible	Yes	Number of Blades	5

Warranty

www.kichler.com/warranty

ALSO IN THIS FAMILY



310073OZ

You can see all products in this family by searching **Kichler.com**