© 2023 Kichler Lighting LLC. All Rights Reserved.



MOTOR FINISH



BLADE FINISHES

Wthrd Med Oak




Damp Rated



Dimmable

HANGING MEASUREMENTS



AR PERFORMANCE

AIRFLOW Cubic Ft. Per Minute on High

6102

RPM Revolutions Per Minute on High

137

POWER USAGE Watts on High (Excludes Lights)

71

AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt

86

SPECIFICATIONS

Performance			
CFM (High) Watts (High)	6102 71	RPM (High) Airflow Efficiency CFM/W (High)	137 86
Motor Specifications			
Amps (High) Motor Type	0.59 AC Induction	Motor Size Primary Material	172MM X 20MM Steel
Mounting/Installation			
Minimum Distance from Fan to Floor Lead Wire Length Low Ceiling Adaptable Connector Mounting Style	7.0 feet 78" No Yes Downrod	Interior/Exterior Location Rating Max Stem Tilt Direct Wire Wire Connectors	EXTERIOR Damp 22.0 Degrees Yes Wire Nuts
Dimensions			
Downrod 1 Downrod 1 - Measurement B Base Backplate Blade Sweep Length	1.00 OD X 4.50" 10.00" 5.9" 56 56.00"	Downrod 1 - Measurement A Downrod 1 - Measurement C Weight Height Width	14.30" 9.60" 25.00 LBS 14.30" 56.00"
Light Source			
Downlight Included Dimmable Kelvin Temperature Diffuser Description	Yes Yes 3000K Frosted	Downlight Option Color Rendering Index Initial Lumens Downward-facing Bulbs	Integrated 90 1400 1 X 17
Photometrics			
Delivered Efficacy (Lumens/Watt)	80		
Electrical			
Input Voltage	120.00V	Supply Wire (Degrees)	90

FIXTURE ATTRIBUTES

Warranty

www.kichler.com/warranty

Compatible Accessories

CoolTouch™ Handheld Control System Full Function White, 65K Wall Transmitter Full Function Multiple Finishes

ALSO IN THIS FAMILY







310080NI 310080SBK 310080WH

You can see all products in this family by searching Kichler.com