@ 2023 Kichler Lighting LLC. All Rights Reserved.

#### **MOTOR FINISH**



Brushed Nickel

## **BLADE FINISHES**

Silver



Dimmable




(LED) LED Light Kit



W Wet Rated

## HANGING MEASUREMENTS



#### **AR PERFORMANCE**

AIRFLOW Cubic Ft. Per Minute on High

6102

Delivered Efficacy (Lumens/Watt)

80

RPM Revolutions Per Minute on High

137

POWER USAGE Watts on High (Excludes Lights)

71

AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt

86

# **SPECIFICATIONS**

| SPECIFICATIONS   |   |  |  |
|--|---|--|--|
| Performance  |   |  |  |
| CFM (High)<br>Watts (High)   | 6102<br>71  | RPM (High)<br>Airflow Efficiency CFMW (High)   | 137<br>86  |
| Motor Specifications   |   |  |  |
| Amps (High)<br>Motor Type  | 0.59<br>AC Induction                              | Motor Size<br>Primary Material   | 172MM X 20MM<br>Stainless Steel                  |
| Mounting/Installation  |   |  |  |
| Minimum Distance from Fan to Floor<br>Lead Wire Length<br>Low Ceiling Adaptable<br>Connector<br>Mounting Style | 7.0 feet<br>78"<br>No<br>Yes<br>Downrod           | Interior/Exterior Location Rating Max Stem Tilt Direct Wire Wire Connectors              | EXTERIOR Wet 22.0 Degrees Yes Wire Nuts          |
| Dimensions   |   |  |  |
| Downrod 1 Downrod 1 - Measurement B Base Backplate Blade Sweep Length  | 1.00 OD X 4.50"<br>10.00"<br>5.9"<br>56<br>56.00" | Downrod 1 - Measurement A Downrod 1 - Measurement C Weight Height Width                  | 14.30"<br>9.60"<br>25.00 LBS<br>14.30"<br>56.00" |
| Light Source   |   |  |  |
| Downlight Included Dimmable Kelvin Temperature Diffuser Description Lamp Included # of Bulbs/LED Modules       | Yes<br>Yes<br>3000K<br>Frosted<br>Integrated<br>1 | Downlight Option Color Rendering Index Initial Lumens Downward-facing Bulbs Light Source | Integrated<br>90<br>1400<br>1 X 17<br>LED        |
| Photometrics   |   |  |  |
|  |   |  |  |

| Electrical  |                                    |  |                               |
|---|------------------------------------|--|-------------------------------|
| Input Voltage                                     | 120.00V                            | Supply Wire (Degrees)                    | 90                            |
| FIXTURE ATTRIBUTES                                |                                    |  |                               |
| Blade Finish & Specs                              |                                    |  |                               |
| Blade Finish 1<br>Blade Pitch<br>Number of Blades | Silver<br>12<br>5                  | Blade Material<br>Blades Included        | ABS<br>Yes                    |
| Included Control                                  |                                    |  |                               |
| Wall Control Included<br>Remote Type              | No<br>371085.00                    | Remote Included<br>Limited/Full Function | Yes<br>Full Function          |
| Product/Ordering Information                      |                                    |  |                               |
| SKU<br>UPC  | 310130Nl<br>783927012850           | Finish<br>Style                          | Brushed Nickel<br>Traditional |
| Housing   |                                    |  |                               |
| Fan Primary Control System<br>Shade Dimensions    | 65K Cooltouch - Full Function 7.2" | Shade Description                        | Glass Shade                   |
| Warranty  |                                    |  |                               |
| www.kichler.com/warranty                          |                                    |  |                               |

CoolTouch™ Handheld Control System Full Function White, 65K Wall Transmitter Full Function Multiple Finishes

# ALSO IN THIS FAMILY

**Compatible Accessories** 



You can see all products in this family by searching **Kichler.com**