© 2021 Kichler Lighting LLC, All Rights Reserved.



### **MOTOR FINISH**



### **BLADE FINISHES**

Whtrd Wht Walnu





### **AR PERFORMANCE**

AIRFLOW Cubic Ft. Per Minute on High

5564

RPM Revolutions Per Minute on High

167

POWER USAGE Watts on High (Excludes Lights) 60

310181WZC

Transitional

AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt 93

CFM (Low) RPM (Low) Watts (Low) 2180 66 11

Weathered Zinc

783927543590

**Product/Ordering Information** 

SKU

Style

SPECIFICATIONS			
Light Source			
Downlight Included Downward-facing Bulbs Watts (Low)	Yes 1 X 17W 11	Downlight Option Watts (High) Dimmable	Integrated 60 Yes
Photometrics			
Color Rendering Index	80	Kelvin Temperature	3000K
Electrical			
Amps (High) Motor Size	0.50 188MM X 25MM	Amps (Low) Motor Type	0.22 AC
Dimensions			
Downrod 1 Weight Width	1.00 OD X 6.00" 35.38 LBS 54.00"	Base Backplate Height	6.25 DIA 20.00"
Mounting/Installation			
Minimum Distance from Fan to Floor Lead Wire Length Mounting Weight	12 feet 78" 35.38 LBS	Interior/Exterior Location Rating	Exterior CSA UL Listed Wet
FIXTURE ATTRIBUTES			

### Housing STEEL Diffuser Description Cased Opal Primary Material Max Stem Tilt 18 Degrees

Finish

UPC

# Blade Finish & Specs

Blade Finish 1WHTRD WHT WALNUBlade MaterialABSBlade Pitch14Blade Sweep54Blades IncludedYesNumber of Blades4

# Warranty

www.kichler.com/warranty

# **ALSO IN THIS FAMILY**







9142BK



9142N



9023OZ



9142OZ

You can see all products in this family by searching Kichler.com