@ 2021 Kichler Lighting LLC. All Rights Reserved.

### **MOTOR FINISH**



## **BLADE FINISHES**

White



Damp Rated

## **AR PERFORMANCE**

AIRFLOW Cubic Ft. Per Minute on High

4367

Minute on High

167

RPM

Revolutions Per

POWER USAGE Watts on High (Excludes Lights) 52

330019WH

Transitional

AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt 84

CFM (Low) RPM (Low) Watts (Low) 1522 57 9

White

783927572231

## **SPECIFICATIONS**

**Product/Ordering Information** 

SKU

Style

Housing

Light Source			
Downlight Option Watts (High)	Integrated 52	Downward-facing Bulbs Watts (Low)	1 X 17 9
Photometrics			
Color Rendering Index	90	Kelvin Temperature	3000K
Electrical			
Amps (High) Motor Size	0.43 153MM X 15MM	Amps (Low) Motor Type	0.07 AC
Dimensions			
Downrod 1 Downrod 1 - Measurement B Base Backplate Height	1.00 OD X 4.00" 7.50" 5.90 DIA 12.50"	Downrod 1 - Measurement A Downrod 1 - Measurement C Weight Width	9.50" 11.50" 17.60 LBS 52.00"
Mounting/Installation			
Interior/Exterior Location Rating Mounting Weight  FIXTURE ATTRIBUTES	Exterior CSA UL Listed Damp 15.09 LBS	Lead Wire Length Low Ceiling Adaptable	78" Yes, Dual Mount Included

#### Remote Included Yes Diffuser Description Frosted White Polycarbonate Primary Material STEEL Max Stem Tilt 22 Degrees

Finish

UPC

Blade Finish & Specs

Blade Finish 1WHITEBlade MaterialWOODBlade Pitch12Blade Sweep52Blades IncludedYesNumber of Blades5

Warranty

www.kichler.com/warranty

# **ALSO IN THIS FAMILY**







330019MWH 330019SBK 330019SNB

You can see all products in this family by searching  ${\bf Kichler.com}$