© 2023 Kichler Lighting LLC. All Rights Reserved.



#### **MOTOR FINISH**



## **BLADE FINISHES**


Natural Brass





(LED) LED Light Kit

## HANGING MEASUREMENTS



## **AR PERFORMANCE**

AIRFLOW Cubic Ft. Per Minute on High

5400

Delivered Efficacy (Lumens/Watt)

75

**RPM** Revolutions Per Minute on High

106

POWER USAGE Watts on High (Excludes Lights)

75

AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt

72

#### **SPECIFICATIONS**

| SPECIFICATIONS   |   |  |  |
|--|---|--|--|
| Performance  |   |  |  |
| CFM (High)<br>Watts (High)   | 5400<br>75  | RPM (High)<br>Airflow Efficiency CFM/W (High)  | 106<br>72  |
| Motor Specifications   |   |  |  |
| Amps (High)<br>Motor Type  | 0.63<br>AC Induction                              | Motor Size<br>Primary Material   | 188MM X 25MM<br>Steel                            |
| Mounting/Installation  |   |  |  |
| Minimum Distance from Fan to Floor<br>Lead Wire Length<br>Low Ceiling Adaptable<br>Connector<br>Mounting Style | 7.0 feet<br>78"<br>No<br>Yes<br>Downrod           | Interior/Exterior<br>Location Rating<br>Max Stem Tilt<br>Direct Wire<br>Wire Connectors  | INTERIOR Dry 22.0 Degrees Yes Wire Nuts          |
| Dimensions   |   |  |  |
| Downrod 1 Downrod 1 - Measurement B Base Backplate Blade Sweep Length  | 1.00 OD X 4.50"<br>10.00"<br>5.9"<br>54<br>56.00" | Downrod 1 - Measurement A Downrod 1 - Measurement C Weight Height Width                  | 14.60"<br>9.50"<br>28.67 LBS<br>14.60"<br>56.00" |
| Light Source   |   |  |  |
| Downlight Included Dimmable Kelvin Temperature Diffuser Description Lamp Included # of Bulbs/LED Modules       | Yes<br>Yes<br>3000K<br>Frosted<br>Integrated<br>1 | Downlight Option Color Rendering Index Initial Lumens Downward-facing Bulbs Light Source | Integrated<br>90<br>2200<br>1 X 23<br>LED        |
| Photometrics   |   |  |  |

| Electrical  |                                    |  |                           |
|---|------------------------------------|--|---------------------------|
| Input Voltage                                     | 120.00V                            | Supply Wire (Degrees)                    | 90                        |
| FIXTURE ATTRIBUTES                                |                                    |  |                           |
| Blade Finish & Specs                              |                                    |  |                           |
| Blade Finish 1<br>Blade Pitch<br>Number of Blades | Natural Brass<br>13<br>5           | Blade Material<br>Blades Included        | ABS<br>Yes                |
| Included Control                                  |                                    |  |                           |
| Wall Control Included<br>Remote Type              | No<br>371085.00                    | Remote Included<br>Limited/Full Function | Yes<br>Full Function      |
| Product/Ordering Information                      |                                    |  |                           |
| SKU<br>UPC  | 330057SBK<br>783927012768          | Finish<br>Style                          | Satin Black<br>Industrial |
| Housing   |                                    |  |                           |
| Fan Primary Control System<br>Shade Dimensions    | 65K Cooltouch - Full Function 9.5" | Shade Description                        | Glass Shade               |

# Warranty

www.kichler.com/warranty

# **Compatible Accessories**

CoolTouch™ Handheld Control System Full Function White

# **ALSO IN THIS FAMILY**





330057BSS 330057WH

You can see all products in this family by searching Kichler.com