© 2021 Kichler Lighting LLC. All Rights Reserved.

MOTOR FINISH



White

BLADE FINISHES

White



Dimmable



(LED) LED Light Kit

AR PERFORMANCE

AIRFLOW Cubic Ft. Per Minute on High

5620

RPM Revolutions Per Minute on High

137

POWER USAGE Watts on High (Excludes Lights) 73

AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt 87

CFM (Low) RPM (Low) Watts (Low)

2029 58 15

SPECIFICATIONS

Light Source			
Downlight Included Watts (High) Dimmable Light Source Optional Light Kit Available	Yes 73 Yes LED Integrated	Downlight Option Watts (Low) Lamp Included # of Bulbs/LED Modules	Integrated 15 Integrated 1
Photometrics			
Color Rendering Index Kelvin Temperature	90 3000K	Delivered Efficacy (Lumens/Watt)	80
Electrical			
Amps (High) Motor Size Supply Wire (Degrees)	0.61 172MM X 20MM 90	Amps (Low) Motor Type	0.28 AC
Dimensions			
Downrod 1 Downrod 1 - Measurement B Base Backplate	1.00" OD X 6.00"" 10.50" 6.75 DIA	Downrod 1 - Measurement A Downrod 1 - Measurement C Weight	14.75" 10.50" 23.80 LBS
Mounting/Installation			
Minimum Distance from Fan to Floor Lead Wire Length Mounting Style	7.0 feet 78" Downrod	Interior/Exterior Location Rating Mounting Weight	Interior Dry 18.30 LBS
FIXTURE ATTRIBUTES			

Product/Orderin	a Information

SKU	330089WH	Finish	White
Style	Transitional	UPC	783927604048

Fan Primary Control System Diffuser Description Max Stem Tilt Blade Finish & Specs Blade Finish 1 Blade Pitch Blade Sincluded Primary Material Blade Sweep Blade Sweep Blade Succes WHITE Blade Sweep Blade Sweep Blade Sweep Blade Sweep System Syst	Housing			
Blade Finish 1 WHITE Blade Material ABS Blade Pitch 12 Blade Sweep 52	Diffuser Description	Frosted White Polycarbonate		
Blade Pitch 12 Blade Sweep 52	Blade Finish & Specs			
	Blade Pitch	12	Blade Sweep	52

Warranty

www.kichler.com/warranty

ALSO IN THIS FAMILY





330089NI 330089SBK

You can see all products in this family by searching ${\bf Kichler.com}$