



Product Number: 20481

Order Abbreviation: CF26DD/841/ECO/BL/1

General Description: 26W DULUX D 2-pin CFL in CP blister card with Designer Premium Cool White packaging graphics.

*** Full Case Required**

Product Information

Abbrev. With Packaging Info.	CF26DD841ECOB1 6/CS 1/SKU
Average Rated Life (hr)	10000
Base	G24D-3
Bulb	T12
Color Rendering Index (CRI)	82
Color Temperature/CCT (K)	4100
Family Brand Name	Dulux® D
Initial Lumens at 25C	1800
Nominal Voltage (V)	105.00
Nominal Wattage (W)	26.00

Footnotes

- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- 2 pin CF lamps are not suitable for use in frequently cycled applications or with occupancy sensors. 2 pin CF lamps should never be installed in 4 pin sockets regardless if lamp will fit.
- Rule of Thumb for Compact Fluorescent Lamps: Divide wattage of incandescent lamp by 4 to determine approximate wattage of compact fluorescent lamp that will provide similar light output.
- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. operating cycles under specified conditions and with ballast meeting ANSI specifications. If operating cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- SYLVANIA ECOLOGIC fluorescent lamps are designed to pass the Federal Toxic Characteristic Leaching Procedure (TCLP) criteria for classification as non-hazardous waste in most states. TCLP test results are available upon request. Lamp disposal regulations may vary, check your local & state regulations. For more information, please visit www.lamprecycle.org
- Mean lumens are measured at 40% of average rated lamp life.
- The lamp should not be in contact with any surface of the luminaire (applies to either high frequency or 60Hz ballasted systems).