1/11/2018 Product Details

Product 25313

Number:

Order F24T12/CW/HO

Abbreviation:

General 35W, 24" MOL, T12 HO (800 mA) rapid start fluorescent lamp, Cool White

Description: phosphor, 4200K color temperature, 60 CRI

SYLVANIA

* Full Case Required

Product Information

Abbrev. With Packaging Info. F24T12CWHO 30/CS 1/SKU

Actual Length (in) 21.909
Actual Length (mm) 556.49
Average Rated Life (hr) 9000

Base Recessed Double Contact

 Bulb
 T12

 Color Rendering Index (CRI)
 60

 Color Temperature/CCT (K)
 4200

 Diameter (in)
 1.593

 Diameter (mm)
 40.46

Industry Standards ANSI C78.81 - 2001

 Initial Lumens at 25C
 1650

 Mean Lumens at 25C
 1337

 Mean Lumens at 35C
 1337

 Nominal Length (in)
 24.000

 Nominal Length (mm)
 609.60

 Nominal Wattage (W)
 35.00

Footnotes

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. operating cycles under specified conditions and with ballast meeting ANSI specifications. If operating cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.