

**Product Number:** 25314

**Order Abbreviation:** F24T12/D/HO

**General Description:** 35W, 24" MOL, T12 HO (800 mA) rapid start fluorescent lamp, Daylight phosphor, 6500K color temperature, 76 CRI



#### Product Information

|                              |                         |
|------------------------------|-------------------------|
| Abbrev. With Packaging Info. | F24T12DHO 30/CS 1/SKU   |
| Actual Length (in)           | 21.909                  |
| Actual Length (mm)           | 556.49                  |
| Average Rated Life (hr)      | 9000                    |
| Base                         | Recessed Double Contact |
| Bulb                         | T12                     |
| Color Rendering Index (CRI)  | 76                      |
| Color Temperature/CCT (K)    | 6500                    |
| Diameter (in)                | 1.593                   |
| Diameter (mm)                | 40.46                   |
| Industry Standards           | ANSI C78.81 - 2001      |
| Initial Lumens at 25C        | 1400                    |
| Mean Lumens at 25C           | 1134                    |
| Mean Lumens at 35C           | 1134                    |
| Nominal Length (in)          | 24.000                  |
| Nominal Length (mm)          | 609.60                  |
| Nominal Wattage (W)          | 35.00                   |



#### Footnotes

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. operating cycles under specified conditions and with ballast meeting ANSI specifications. If operating cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.