

Product Number: 27358

Order Abbreviation: F30T12 D RS CP

General Description: 30W, T12 rapid start fluorescent lamp, Daylight phosphor, 6500K color temperature, 76 CRI Retail Pack 30Bulbs per Case 1Bulb per Pack



Product Information

Abbrev. With Packaging Info.	F30T12DRSCP 30/CS 1/SKU
Actual Length (in)	35.780
Actual Length (mm)	908.81
Average Rated Life (hr)	18000
Base	Medium Bipin
Bulb	T12
Color Rendering Index (CRI)	76
Color Temperature/CCT (K)	6500
Diameter (in)	1.591
Diameter (mm)	40.40
Initial Lumens at 25C	1900
Mean Lumens at 25C	1615
Nominal Length (in)	36.000
Nominal Length (mm)	914.40
Nominal Wattage (W)	30.00



Footnotes

- Average rated life is measured at 3 hours per start on 2-lamp, rapid start magnetic ballasts per IES recommended practice. Lamp life on single-lamp rapid start ballasts may be reduced.
- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. operating cycles under specified conditions and with ballast meeting ANSI specifications. If operating cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.