

Product Number:

24755

Order Abbreviation:

F40/DAYLIGHTFULLSPECTRUM

General Description:

40W, 48 inch MOL, T12, rapid start fluorescent lamp, Designer's Choice, Daylight Full Spectrum phosphor, 5000K color temperature, 90 CRI, 2 lamps packed in dual end caps, 30 per case. VIVID Color: High CRI lamps for color critical applications.



* Full Case Required

Product Information

Abbrev. With Packaging Info.	F40DAYLIGHTFULLSPECTRUM 30/CS 2/SKU
Actual Length (in)	48.000
Actual Length (mm)	1219.20
Average Rated Life (hr)	20000
Base	Medium Bipin
Bulb	T12
Color Rendering Index (CRI)	90
Color Temperature/CCT (K)	5000
Diameter (in)	0.000
Diameter (mm)	0.00
Family Brand Name	Daylight Full Spectrum
Initial Lumens at 25C	2200
Nominal Length (in)	48.000
Nominal Length (mm)	1219.20
Nominal Wattage (W)	40.00



Footnotes

- Average life rating at 12 hours operation per start is 28,800 hours.
- Average rated life is measured at 3 hours per start on 2-lamp, rapid start magnetic ballasts per IES recommended practice. Lamp life on single-lamp rapid start ballasts may be reduced.
- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. operating cycles under specified conditions and with ballast meeting ANSI specifications. If operating cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- The "RS" designation has been eliminated to simplify the ordering abbreviation.
- 40W Rapid Start Lamps may be used in starter operated fixtures designed for 40W preheat lamps. Life rating for preheat service is approximately 15,000 hours average.