




Color :  Brown

UPC Code : 078477830741

Country Of Origin : Mexico

NEMA :  5-20R

Available Colors :



21254

20 Amp 4-in-1 Quadruplex Receptacle/Outlet, Industrial Grade

4-in-1 Quadruplex Receptacle Outlet, Heavy-Duty Industrial Specification Grade, 20 Amp, 125 Volt, Side Wire, NEMA 5-20R, 2-Pole, 3-Wire - Brown

Leviton's line of Heavy-Duty Industrial Grade receptacles are available with a number of wiring options and features. The beauty, durability and versatility of Decora® devices and surge suppression receptacles are perfect for a variety of industrial applications.

- Code Compliant - Allows you to increase the number of receptacles in your facility without having to pull new wires
- Durable - Impact and chemical resistant nylon cover and base
- Easy Installation - Termination anchor holes for easy conductor wiring
- Reliable - 10-Year Limited Warranty

Technical Information

AC Horsepower Ratings

At Rated Voltage : 1 HP

Electrical Specifications

Amperage : 20 A

Current Limiting : Full Rated Current

Dielectric Voltage :
Withstands 2000V per UL498

Grounding : Grounding

Pole : 2

Temperature Rise : Max 30C
after 50 cycles OL at 150
percent rated current

Voltage : 125 VAC

Wire : 3

Environmental Specifications

Flammability : Rated V-2 per
UL 94

Operating Temperature : -40°
C to 60°C

Material Specifications

Body Material : Nylon

Color : Brown

Face Material : Nylon

Grounding Screw : Plated
Steel

Line Contacts : Phosphor
Bronze

Strap Material : Galvanized
Steel with Riveted Ground
Contacts

Terminal Screws : Plated
Brass

Mechanical Specifications

Product ID : Ratings are
permanently marked on device

Screw Terminal Torque : 10-
12 in-lbs

Terminal Accom. : 14-12 AWG

Terminal ID : Brass-Hot,
Green-Ground, Silver-Neutral

Termination : Side Wire

Torque Range : 12-14 inch
pounds

Standards and Certifications

ANSI : C-73

CSA C22.2 No. 42 : File
152105

NEMA : WD-1 WD-6

NOM : 057

UL498 : File E13399

Warranty : 10-Year Limited

Product Features

Brand : 4-in-1

Color : Brown

Device Type : Quadruplex
Receptacle Outlet

Grade : Heavy-Duty Industrial
Specification Grade

NEMA : 5-20R

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·
FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 ·

Visit our Website at: www.leviton.com

© 2025 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/company/about-leviton/locations

© 2025 Leviton Manufacturing Co., Inc.