



UPC Code : 078477806326

Country Of Origin : Mexico

NEMA :  L14-20R

2416

20 Amp, 125/250 Volt, Flanged Outlet Locking Receptacle, Industrial Grade

20 Amp, 125/250 Volt, NEMA L14-20R, 3P, 4W, Flanged Outlet Locking Receptacle, Industrial Grade, Grounding - WHITE

ROHS Compliant : Yes

- One piece contacts reduce friction and overheating
- Rugged nylon construction resists impact, sunlight, chemicals, and rough use
- Ratings and NEMA I.D. permanently marked on device
- Industry exclusive limited lifetime warranty

Technical Information

AC Horsepower Ratings

At Rated Voltage : 2 HP L-L /
1 HP L-N

Electrical Specifications

Amperage : 20 A

Current Limiting : Full Rated Current

Dielectric Voltage :
Withstands 2000V per UL498

Grounding : Grounding

Pole : 3

Temperature Rise : Max 30C
after 250 cycles OL at 200
percent rated current

Voltage : 125/250 VAC

Wire : 4

Environmental Specifications

Environment : Dry

Flammability : Rated V-2 per
UL 94

Operating Temperature : -40°
C to 60°C

Material Specifications

Body Material : Nylon

Color : White

Face Material : Nylon

Grounding Screw : Brass 8-32

Line Contacts : Solid Brass

Strap Material : Thermoplastic
Nylon

Terminal Screws : Brass 10-32

Mechanical Specifications

Product ID : Ratings and
NEMA I.D. permanently marked
on device

Screw Terminal Torque : 10-
14 in-lbs

Terminal Accom. : 18-10 AWG

Product Features

Brand : Black and White

Color : White

Device Type : Locking Flanged
Outlet

NEMA : L14-20R

Terminal ID : Brass-Hot,
Green-Ground, Silver-Neutral

Termination : Back

Standards and Certifications

ANSI : C-73

CSA C22.2 No. 42 : File LR-406

NEMA : WD-6


NOM : 057

UL Fed Spec WC-596 : File
E13393

UL498 : File E13393

Warranty : Limited Lifetime
Warranty

Wiring Diagram



Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·
FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 ·

Visit our Website at: www.leviton.com

© 2025 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/company/about-leviton/locations

© 2025 Leviton Manufacturing Co., Inc.