



5292

15 Amp Duplex Receptacle/Outlet, Industrial Grade, Dual Voltage, Self-Grounding

Duplex Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Dual Voltage, Smooth Face, 15 Amp, 125/250 Volt, Side Wire, NEMA 5-15R_6-15R, 2-Pole, 3-Wire, Self-Grounding - Brown

ROHS Compliant : Yes

Leviton's line of Extra Heavy-Duty Industrial Grade receptacles are designed and manufactured to withstand the harsh conditions typically associated with industrial environments. Available in a wide variety of configurations, including isolated ground, tamper-resistant, hospital grade, etc., these Industrial Grade devices are the electrical contractor's choice for use in factories, schools, hospitals and commercial office buildings.

Color :  Brown

UPC Code : 078477901724

Country Of Origin : Mexico

NEMA :  5-15R_6-15R

Available Colors :


Ivory

Technical Information

AC Horsepower Ratings

At Rated Voltage : 1/2 HP
125V / 1-1/2 HP 250V

Electrical Specifications

Amperage : 15 A

Current Limiting : Full Rated Current

Dielectric Voltage :
Withstands 2000V per UL498

Grounding : Self-Grounding

Pole : 2

Temperature Rise : Max 30C
after 250 cycles OL at 200
percent rated current

Voltage : 125/250 VAC

Wire : 3

Environmental Specifications

Flammability : Rated V-2 per
UL 94

Operating Temperature : -40°
C to 60°C

Material Specifications

Body Material : Thermoplastic
Nylon

Color : Brown

Face Material : Thermoplastic
Nylon

Ground Clips : Brass

Grounding Screw : Plated
Steel

Line Contacts : Phosphor
Bronze

Strap Material : Galvanized
Steel with Riveted Ground
Contacts

Terminal Screws : Plated
Brass

Mechanical Specifications

Product ID : Ratings are permanently marked on device

Screw Terminal Torque : 14-16 in-lbs

Terminal Accom. : 14-10 AWG

Terminal ID : Brass-Hot, Green-Ground, Silver-Neutral

Termination : Side Wire

Torque Range : 14-16 inch pounds

Product Features

Body Material : Thermoplastic Nylon

Color : Brown

Device Type : Duplex Receptacle Outlet

Face Material : Thermoplastic Nylon

Feature 3 : Dual Voltage

Feature 4 : Smooth Face

Grade : Heavy-Duty Industrial Specification Grade

Grounding : Self-Grounding

NEMA : 5-15R_6-15R

Standards and Certifications

ANSI : C-73

CSA C22.2 No. 42 : File 152105

NEMA : WD-6


NOM : 057

UL Fed Spec WC-596 : File E13399


UL498 : File E13399

Warranty : 10-Year Limited

Wiring Diagram



6-15R



5-15R

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·
FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 ·

Visit our Website at: www.leviton.com

© 2025 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/company/about-leviton/locations

© 2025 Leviton Manufacturing Co., Inc.