



UPC Code : 078477066249

Country Of Origin : Mexico

NEMA :  5-20R

60W33

Wetguard Watertight Flip Lid with Single Receptacle

20 Amp, 125 Volt, NEMA 5-20R, 2P, 3W, Flip Lid with Receptacle, Narrow Body Single Receptacle, Straight Blade, Industrial Grade, Grounding, Wetguard Flip Lid, Side Wired, Nickel-Plated Brass Strap, - YELLOW

- BATTLE THE ELEMENTS- Resistant to water, acids, alkalies, and many automotive and industrial lubricants and solvents.
- ADVANCED LID DESIGN- Our spring-loaded flip lid is impact and chemical resistant with a Valox® PBT cover
- MORE SECURE- Dual-hasp provides additional lockout /tagout option for added security.
- DURABLE- Ideal for harsh environments with added resistance against heat, chemical corrosion, and physical abrasion

Technical Information

AC Horsepower Ratings

At Rated Voltage : 1 HP

Electrical Specifications

Amperage : 20 A

Current Limiting : Full Rated Current

Dielectric Voltage :
Withstands 2000V per UL498

Grounding : Grounding

Pole : 2

Temperature Rise : Max 30C
after 250 cycles OL at 200
percent rated current

Voltage : 125 VAC

Wire : 3

Environmental Specifications

Flammability : Rated V-2 per
UL 94

Operating Temperature : -40°
C to 60°C

Material Specifications

Assembly Screws : Stainless
Steel 300

Blades/Contacts : Nickel-
Plated Brass

Body Material : Thermoplastic
Nylon

Bushing : Santoprene TPV

Clamp Nuts : Nickel-Plated
Brass

Color : Yellow

**Compression Nut, Strain
Relief :** Nylon

Face Material : Thermoplastic
Nylon

Grounding Screw : Nickel-
Plated Brass 8-32

Line Contacts : Nickel-Plated
Brass Triple-Wipe

Terminal Screws : Nickel-
Plated Brass

UL498 : File E13399

Wire Module : Thermoplastic

Yoke : Nickel-Plated Brass

Mechanical Specifications

Cord Range : .375 - .655

Product ID : Ratings and
NEMA I.D. permanently marked
on device

Terminal Accom. : 18-10 AWG

Terminal ID : Brass-Hot,
Green-Ground, Silver-Neutral

Product Features

Body Material : Thermoplastic
Nylon

Brand : Wetguard

Color : Yellow

Device Type : Straight Blade
Outlet

Face Material : Thermoplastic
Nylon

NEMA : 5-20R

Strap Material : Nickel-Plated
Brass

Termination : Back

Standards and Certifications

ANSI : C-73

CSA C22.2 No. 42 : File LR-406

NEMA : WD-6


NOM : 057

UL : 498

UL Fed Spec WC-596 : File
E13399

Warranty : Limited Lifetime
Warranty

Wiring Diagram



SPECIFICATION SUBMITTAL

JOB NAME: 	CATALOG NUMBERS: 	
JOB NUMBER: 		

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.