

# 60W48



**UPC Code :** 078477066270

**Country Of Origin :** Mexico

**NEMA :**  6-20R

Wetguard Watertight Flip Lid with Single Receptacle

20 Amp, 250 Volt, NEMA 6-20R, 2P, 3W, Flip Lid with Receptacle, Narrow Body Single Receptacle, Straight Blade, Industrial Grade, Grounding, Wetguard Flip Lid, Side Wired, Nickel-Plated Brass Strap, - YELLOW

- BATTLE THE ELEMENTS- Resistant to water, acids, alkalis, and many automotive and industrial lubricants and solvents.
- ADVANCED LID DESIGN- Our spring-loaded flip lid is impact and chemical resistant with a Valox® PBT cover
- MORE SECURE- Dual-hasp provides additional lockout /tagout option for added security.
- DURABLE- Ideal for harsh environments with added resistance against heat, chemical corrosion, and physical abrasion

## Technical Information

### AC Horsepower Ratings

**At Rated Voltage :** 2 HP

### Electrical Specifications

**Amperage :** 20 A

**Current Limiting :** Full Rated Current

**Dielectric Voltage :**  
Withstands 2000V per UL498

**Grounding :** Grounding

**Pole :** 2

**Temperature Rise :** Max 30C  
after 250 cycles OL at 200  
percent rated current

**Voltage :** 250 VAC

**Wire :** 3

### Environmental Specifications

**Flammability :** Rated V-2 per  
UL 94

**Operating Temperature :** -40°  
C to 60°C

### Material Specifications

**Assembly Screws :** Stainless  
Steel 300

**Blades/Contacts :** Nickel-  
Plated Brass

**Body Material :** Thermoplastic  
Nylon

**Bushing :** Santoprene TPV

**Clamp Nuts :** Nickel-Plated  
Brass

**Color :** Yellow

**Compression Nut, Strain  
Relief :** Nylon

**Face Material :** Thermoplastic  
Nylon

**Grounding Screw :** Nickel-  
Plated Brass 8-32

**Line Contacts :** Nickel-Plated  
Brass Triple-Wipe

**Terminal Screws :** Nickel-  
Plated Brass

**UL498 :** File E13399

**Wire Module :** Thermoplastic

**Yoke :** Nickel-Plated Brass

#### Mechanical Specifications

**Cord Range :** .375 - .655

**Product ID :** Ratings and  
NEMA I.D. permanently marked  
on device

**Terminal Accom. :** 18-10 AWG

**Terminal ID :** Brass-Hot,  
Green-Ground, Silver-Neutral

#### Product Features

**Body Material :** Thermoplastic  
Nylon

**Brand :** Wetguard

**Color :** Yellow

**Device Type :** Straight Blade  
Outlet

**Face Material :** Thermoplastic  
Nylon

**NEMA :** 6-20R

**Strap Material :** Nickel-Plated  
Brass

**Termination :** Back

#### Standards and Certifications

**ANSI :** C-73

**CSA C22.2 No. 42 :** File LR-406

**NEMA :** WD-6


**NOM :** 057

**UL :** 498

**UL Fed Spec WC-596 :** File  
E13399

**Warranty :** Limited Lifetime  
Warranty

## Wiring Diagram



SPECIFICATION SUBMITTAL

|                            |                                             |             |
|----------------------------|---------------------------------------------|-------------|
| JOB NAME:<br><div></div>   | CATALOG NUMBERS:<br><div></div> <div></div> |             |
| JOB NUMBER:<br><div></div> | <div></div>                                 | <div></div> |

**Leviton Manufacturing Co., Inc**  
201 North Service Road, Melville, NY 11747  
Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.  
T. Monday-Friday): +1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**  
165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·  
FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**  
Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)  
5386- 1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

**Visit our Website at: [www.leviton.com](http://www.leviton.com)**  
© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without  
notice.

**Leviton has a global presence.**  
If you would like to know where your local Leviton office is located please go to:  
[www.leviton.com/international/contacts](http://www.leviton.com/international/contacts)

**© 2024 Leviton Manufacturing Co., Inc.**