

Maintained and Momentary Contact Extra Heavy-Duty Specification Grade
Features and Benefits

- Positive switching action with center-off position
- Large silver cadmium-oxide contacts for long life prevent sticking, welding and excessive pitting
- Clamp-type terminals accept up to #10 CU wire
- Full rated current capacity on fluorescent, tungsten and resistive loads; motor load capacity up to 80% switch current rating
- Backed by a limited 10-year warranty

Back and Side Wired — Maintained Contact Toggle Switches

Rating		15A-120/277V AC	20A-120/277V AC	30A-120/277V AC
Description	Color	Cat. No.	Cat. No.	Cat. No.
Single Pole,	White	1281-W	1285-W	—
Double Throw,	Ivory	1281-I	1285-I	1287-I
Center Off	Lt. Almond	—	1285-T	—
	Gray	—	1285-GY	—
	Brown	1281	1285	1287
	Red	—	1285-R	—
Single Pole, Double	Black	1281-L	1285-L	1287-L
Throw, Center Off,				
Tamper Resistant* (locking)				
Double Pole,	White	1282-W	1286-W	1288-W
Double Throw,	Ivory	1282-I	1286-I	1288-I
Center Off	Brown	1282	1286	1288
Double Pole, Double	Black	—	—	1288-L
Throw, Center Off,				
Tamper Resistant* (locking)				
*Key for Tamper Resistant Switch		55500-PRT		



1281-L



1256



1257-L

Back and Side Wired — Momentary Contact Toggle Switches

Rating		15A-120/277V AC	20A-120/277V AC	30A-120/277V AC
Description	Color	Cat. No.	Cat. No.	Cat. No.
Single Pole,	White	1256-W	1257-W	—
Double Throw,	Ivory	1256-I	1257-I	—
Center Off	Light Almond	—	1257-T	—
	Gray	1256-GY	1257-GY	—
	Brown	1256	1257	1260
	Red	—	1257-R	—
Single Pole,	Black	—	1257-L	—
Double Throw,				
Center Off,				
Tamper Resistant* (locking)				
Double Pole,	Brown	—	—	1262
Double Throw,				
Center Off				
*Key for Tamper Resistant Switch		55500-PRT		