

Leviton Security & Automation Serial Server

93A00-1

RS232/RS485 to TCP/IP converter integrated with a robust system and network management features designed for serial equipment to be accessed and controlled via Intranet or Internet.



KNX® Gateway

97A00-1

The Leviton Security & Automation KNX® Gateway allows Omni and Lumina controllers (OmniPro II, Omni IIe, Omni LTc, Lumina Pro, and Lumina) to communicate with and control KNX® devices installed on the network. Lighting, temperature and energy management, and motors (window coverings, shades, shutters, etc.) are among the many KNX® devices that can be controlled from a Leviton Security & Automation interface or via controller programming.



Serial PC Cable

21A05-2

7 foot cable, modular to DB-9F - connects Omni or Lumina controller serial ports to computer RS-232 serial port for use with PC Access, and other Leviton Security & Automation Connectivity Partners.



UPB™ Powerline Interface Module to Computer Cable

36A05-2

7-foot cable, modular to DB-9F - connects Leviton Security & Automation UPB™ Powerline Interface Module to computer RS-232 serial port for use with UPStart software. UPStart may be downloaded for free. Also used for Leviton Security & Automation Connectivity Partners, as directed.



Serial Connectivity Cable

36A05-4

7-foot cable, modular to DB-9M - connects controller to serial ports for Russound, NuVo, RadioRA, Centralite, Jandy, and other Leviton Security & Automation Connectivity Partners.

