

# LNR80-2E



15 Amp Rhino-Hide® Straight Blade Plug, Industrial Grade

15 Amp, 250 Volt, NEMA 6-15P, 2P, 3W, Plug, Straight Blade, Industrial Grade, Grounding, Rhino-Hide - BLACK

Rhino-Hide from Leviton raises the bar when it comes to industrial grade NEMA configured wiring devices! Boasting the highest watertight ratings of any device in their class – submersible (IP68) and suitable for high pressure/high temperature washdown (IP69K) - no other device of this type on the market even comes close to this level of performance

UPC Code : 078477693629

Country Of Origin : United States

NEMA :  6-15P

## Technical Information

### Electrical Specifications

**Amperage** : 15 A

**Current Limiting** : Full Rated Current

**Dielectric Voltage** :  
Withstands 2000V per UL498

**Pole** : 2

**Temperature Rise** : Max 30C  
after 250 cycles OL at 200  
percent rated current

**Voltage** : 250 VAC

**Wire** : 3

### Material Specifications

**Assembly Screws** : Stainless Steel, Non-Magnetic

**Blades/Contacts, Terminal Clamps** : Electroless Nickel-coated Brass

**Body Material** : Nylon

**Husk** : High-performance TPV

**Terminal Screws** : Electroless Nickel-coated Brass

**Wiring Module** : Nylon

### Product Features

**Brand** : Rhino-Hide

**Color** : Black

**Device Type** : Straight Blade Plug

**NEMA** : 6-15P

### Environmental Specifications

**Enclosure Rating** : NEMA 3R, 4, 4X, 6, 6P, 12, 13; IEC IP66, IP67, IP68, IP69K

**Environment** : Wet

**Operating Temperature** : -40° C to 60°C

### Mechanical Specifications

**Cord Grip Range (in)** : .375-.670

**Product ID** : Ratings and NEMA I.D. permanently marked on device

**Terminal Accom.** : #18 AWG to # 10 AWG

### Standards and Certifications

**ANSI** : C-73

**CSA** : C22.2 No. 42

**NEMA** : WD-6


**NOM** : NOM-ANCE

**UL** : 498

### Warranty

**Warranty** : Limited Lifetime  
Warranty

## Dimensional Drawing



### SPECIFICATION SUBMITTAL

<b>JOB NAME:</b> <input type="text"/>	<b>CATALOG NUMBERS:</b> <input type="text"/>
<b>JOB NUMBER:</b> <input type="text"/>	<input type="text"/>

#### Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.  
T. Monday-Friday): +1-800-824-3005

#### Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·  
FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

#### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)  
5386- 1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

#### Visit our Website at: [www.leviton.com](http://www.leviton.com)

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without  
notice.

#### Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:  
[www.leviton.com/international/contacts](http://www.leviton.com/international/contacts)

© 2024 Leviton Manufacturing Co., Inc.