



# LNR86-5Y

15 Amp Rhino-Hide® Locking Connector, Industrial Grade

15 Amp, 125 Volt, NEMA L5-15R, 2P, 3W, Connector, Locking, Industrial Grade, Grounding, Rhino-Hide - YELLOW

Rhino-Hide from Leviton raises the bar when it comes to industrial grade NEMA configured wiring devices! Boasting the highest watertight ratings of any device in their class – submersible (IP68) and suitable for high pressure/high temperature washdown (IP69K) - no other device of this type on the market even comes close to this level of performance

UPC Code : 078477692899

Country Of Origin : United States

NEMA :  L5-15R

## Technical Information

### Electrical Specifications

**Amperage** : 15 A

**Current Limiting** : Full Rated Current

**Dielectric Voltage** :  
Withstands 2000V per UL498

**Pole** : 2

**Temperature Rise** : Max 30C  
after 250 cycles OL at 200  
percent rated current

**Voltage** : 125 VAC

**Wire** : 3

### Environmental Specifications

**Enclosure Rating** : NEMA 3R,  
4, 4X, 6, 6P, 12, 13; IEC IP66,  
IP67, IP68, IP69K

**Environment** : Wet

**Operating Temperature** : -40°  
C to 60°C

### Material Specifications

**Assembly Screws** : Stainless  
Steel, Non-Magnetic

**Blades/Contacts, Terminal  
Clamps** : Electroless Nickel-  
coated Brass

**Body Material** : Nylon

**Husk** : High-performance TPV

**Terminal Screws** : Electroless  
Nickel-coated Brass

**Wiring Module** : Nylon

### Mechanical Specifications

**Cord Grip Range (in)** : .375-  
.670

**Product ID** : Ratings and  
NEMA I.D. permanently marked  
on device

**Terminal Accom.** : #18 AWG  
to # 10 AWG

### Product Features

**Brand** : Rhino-Hide

**Color** : Yellow

**Device Type** : Locking  
Connector

**NEMA** : L5-15R

### Standards and Certifications

**ANSI** : C-73

**CSA** : C22.2 No. 42

**NEMA** : WD-6

**NOM** : NOM-ANCE

**UL** : 498

### Warranty

**Warranty : Limited Lifetime  
Warranty**

**SPECIFICATION SUBMITTAL**

|                                            |                                                 |                      |
|--------------------------------------------|-------------------------------------------------|----------------------|
| <b>JOB NAME:</b><br><input type="text"/>   | <b>CATALOG NUMBERS:</b><br><input type="text"/> | <input type="text"/> |
| <b>JOB NUMBER:</b><br><input type="text"/> | <input type="text"/>                            | <input type="text"/> |

**Leviton Manufacturing Co., Inc**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)

5386- 1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

**Visit our Website at: [www.leviton.com](http://www.leviton.com)**

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:

[www.leviton.com/international/contacts](http://www.leviton.com/international/contacts)

© 2024 Leviton Manufacturing Co., Inc.