

LNR96-6

15 Amp Rhino-Hide® Locking Receptacle, Industrial Grade

15 Amp, 250 Volt, NEMA L6-15R, 2P, 3W, Receptacle, Locking, Industrial Grade, Grounding, Rhino-Hide - GRAY

Rhino-Hide from Leviton raises the bar when it comes to industrial grade NEMA configured wiring devices! Boasting the highest watertight ratings of any device in their class – submersible (IP68) and suitable for high pressure/high temperature washdown (IP69K) - no other device of this type on the market even comes close to this level of performance



UPC Code : 078477693070

Country Of Origin : United States

NEMA :  L6-15R

Technical Information

Electrical Specifications

Amperage : 15 A

Current Limiting : Full Rated Current

Dielectric Voltage :
Withstands 2000V per UL498

Pole : 2

Temperature Rise : Max 30C
after 250 cycles OL at 200
percent rated current

Voltage : 250 VAC

Wire : 3

Environmental Specifications

Enclosure Rating : NEMA 3R,
4, 4X, 6, 6P, 12, 13; IEC IP66,
IP67, IP68, IP69K

Environment : Wet

Operating Temperature : -40°
C to 60°C

Material Specifications

Assembly Screws : Stainless
Steel, Non-Magnetic

**Blades/Contacts, Terminal
Clamps** : Electroless Nickel-
coated Brass

Receptacle Housing : Coated
Die-Cast Aluminum

Terminal Screws : Electroless
Nickel-coated Brass

Wiring Module : Nylon

Mechanical Specifications

Cord Grip Range (in) : .375-
.670

Product ID : Ratings and
NEMA I.D. permanently marked
on device

Terminal Accom. : #18 AWG
to # 10 AWG

Product Features

Brand : Rhino-Hide

Color : Gray

Device Type : Locking
Receptacle

NEMA : L6-15R

Standards and Certifications

ANSI : C-73

CSA : C22.2 No. 42

NEMA : WD-6

NOM : NOM-ANCE

UL : 498

Warranty

Warranty : Limited Lifetime
Warranty

Patents*

CA2866061

US9496696

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

SPECIFICATION SUBMITTAL

JOB NAME: 	CATALOG NUMBERS: 	
JOB NUMBER: 		

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.