



Color :  Red

UPC Code : 078477705438

Country Of Origin : Mexico

Available Colors :



TDR15-R

Tamper-Resistant Decora Plus Receptacle, 15 Amp, 125 Volt

Decora Plus Duplex Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Tamper-Resistant, Smooth Face, 15 Amp, 125 Volt, Back or Side Wire, NEMA 5-15R, 2-Pole, 3-Wire, Self-Grounding - Red

Technical Information

AC Horsepower Ratings

At Rated Voltage : 1/2 HP

Flammability : Rated V-2 per UL 94

Operating Temperature : -40° C to 75°C

Electrical Specifications

Amperage : 15 A

Body Material : Nylon

Clamp Nuts : Zinc-Plated Steel

Color : Red

Current Limiting : Full Rated Current

Dielectric Voltage :
Withstands 2000V per UL498

Face Material : Nylon

Ground Clips : Brass-Plated

Grounding : Self-Grounding

Grounding Screw : Brass 8-32

Line Contacts : Phosphor Bronze Triple Wipe 0.031

Pole : 2

Strap Material : Zinc-Plated Steel

Temperature Rise : Max 30C after 250 cycles OL at 200 percent rated current

Terminal Screws : Brass 10-32

Voltage : 125 VAC

Wire : 3

Environmental Specifications

Flammability : Rated V-2 per UL 94

Operating Temperature : -40° C to 75°C

Product ID : Ratings are permanently marked on device

Terminal Accom. : 14-10 AWG

Terminal ID : Brass-Hot, Green-Ground, Silver-Neutral

Material Specifications

Body Material : Nylon

Brand : Decora Plus

Clamp Nuts : Zinc-Plated Steel

Color : Red

Device Type : Duplex Receptacle Outlet

Face Material : Nylon

Feature 2 : Tamper-Resistant

Termination : Back or Side Wire

Feature 4 : Smooth Face

Grade : Heavy-Duty Industrial Specification Grade

Ground Clips : Brass-Plated

Grounding Screw : Brass 8-32

Line Contacts : Phosphor Bronze Triple Wipe 0.031

Strap Material : Zinc-Plated Steel

Terminal Screws : Brass 10-32

Mechanical Specifications

ANSI : C-73

CSA C22.2 No. 42 : File 152105

NOM : 057

Product ID : Ratings are permanently marked on device

Screw Terminal Torque : 14-18 in-lbs

Terminal Accom. : 14-10 AWG

Terminal ID : Brass-Hot, Green-Ground, Silver-Neutral

Termination : Back or Side Wire

UL 498 : File E13399

Warranty : 10-Year Limited

Product Features

At Rated Voltage : 1/2 HP

Brand : Decora Plus

Color : Red

Device Type : Duplex Receptacle Outlet

Feature 2 : Tamper-Resistant

Feature 4 : Smooth Face

Grade : Heavy-Duty Industrial Specification Grade

Standards and Certifications

ANSI : C-73

CSA C22.2 No. 42 : File 152105

NOM : 057

UL 498 : File E13399

Warranty : 10-Year Limited

Warranty

Amperage : 15 A

Current Limiting : Full Rated Current

Dielectric Voltage : Withstands 2000V per UL498

Grounding : Self-Grounding

Pole : 2

Temperature Rise : Max 30C after 250 cycles OL at 200 percent rated current

Voltage : 125 VAC

Warranty : 10-Year Limited

Wire : 3

Patents *

CA2621644

CA2677283

US7355117

CA2624409

MX321216

US7820909

US7868719
US8684771

US8242362

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·
FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 ·

Visit our Website at: www.leviton.com

© 2025 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/company/about-leviton/locations

© 2025 Leviton Manufacturing Co., Inc.