LED-8024 Post Top / Site / Wall Pack

SKU (USA) SKU (Canada)

LED-8024E30 LED-8024E30C 45W 3000K LED-8024E42 LED-8024E42C 45W 4200K

LED-8024E57 LED-8024E57C 45W 5700K




Technical Specifications			
Models US/CAN	LED-8024E30/ LED-8024E30C	LED-8024E42/ LED-8024E42C	LED-8024E57/ LED-8024E57C
ССТ	3000K	4200K	5700K
Power Consumption	45 watts		
Replaces	175w MH/HPS		
Mounting	E26		
Voltage	120-277VAC (USA) 120-347VAC (CANADA)		
LED Type	176 Samsung #5630 SMD		
Beam Angle	360		
Dimmable	No		
Operating Temp	-40°F - +122°F		
Rated R70 Life	Up to 50,000 Hrs.		
Warranty	5 Year Limited*		
LM79 Specifications	N/A	Yes	Yes
Power (W)	44.4	45.1	45.1
ССТ	3273	4302	5610
Light Output	4969	5361	5037
Efficacy	111.9	118	111.6
THD @ 277V	11.70%	11.30%	12.74%
PF @ 277V	0.938	0.935	0.934
CRI:	84.4	84.4	86
R9	15	16	34
	-0.0015	-0.0001	-0.0026
Duv	-0.0013		
Duv Packaging		Master Ca	rton
	9/1	Master Car " x 11.42"	

Note: All specification information falls within a \pm 2% range and is subject to change without notice.

NOTE: Light Efficient Design is providing this information to the general public. Please note that all products contained herein are trademarked, copyrighted, and/or have patents pending. Any use of these designs is strictly prohibited without prior written consent. Light Efficient Design protects its proprietary information vigorously in the courts of the United States of America.











Description:

45W LED retrofit lamp to replace MH and HPS lamps up to 175w, E26 Medium base. Integrated insect/dust screen. UL damp rated, approved for <u>fully enclosed</u> fixtures.

Features:

- Replaces 175w HID Lamps
- 120-277V or 120-347V (Canada)
- UL Classified for damp environments (USA & Canada)
- UL approved for fully enclosed fixtures (USA & Can)
- Active Cooling Fan >70,000 hr. rated life
- 50,000 rated life
- 5 year limited warranty (see website for details)

Applications:







Wall Pack

Shoe Box

Post Top

Installation Notes:

- When installing LED-8000 series retrofit lamps within HID fixtures, ballast must be bypassed when present.
- 8000 series retrofits are UL damp rated, sealing the fixtures after installation will deliver best results.
- Installing surge/lightning protectors is highly recommended and helps to eliminate premature driver failure caused by surges and other power fluctuations.



188 S. Northwest Highway • Cary, IL 60013 (847) 380-3540 • FAX: (847) 380-3542 www.led-llc.com