

POST TOP RETROFITS 360° OMNI DIRECTIONAL DESIGN




120-277V

VOLTAGE**



E26/EX39


MEDIUM +
MOGUL BASES



ULTYPE B

BALLAST
BYPASS

INSTALL METHOD



-40°F TO 122°F

OPERATING TEMP



ACTIVE
COOLING



6kA

SURGE
PROTECTION



80+

CRI



L70
50,000

RATED LIFE



5
YEAR
WARRANTY

WARRANTY

versatility & quality



runs
cooler
so it lasts
longer

- Available in 35W, 45W, 65W & 100W models replacing up to 400W HID.
- Advanced active cooling. Energetic cooling fan & dynamic temp control supports a longer, brighter life.
- Multi-directional mounting capability & 360° design. Use base down, base up or base sideways without affecting performance.
- Pretested & potted drivers are burnt in 3x prior to shipping and protected against vibration & moisture.
- Expertly engineered to work efficiently in enclosed fixtures & damp environments, while also protected against insects & dust.
- Dual stage MOV protection with integrated 6kA surge.
- USA designed & specified LED driver.


PART #	UPC	REPLACES	WATTAGE	LUMENS	LPW	CCT (K)*	BASE
LED-8033E57-A	844006081119	175W	35W	5617	160	5700K	E26
LED-8033M57-A	844006083366	175W	35W	5237	150	5700K	EX39
LED-8024E57-A	844006080242	250W	45W	6619	147	5700K	E26
LED-8024M57-A	844006083366	250W	45W	6632	147	5700K	EX39
LED-8046M57-A	844006081775	320W	65W	9499	146	5700K	EX39
LED-8027M57-A	844006080273	400W	100W	14613	146	5700K	EX39

* See page 2 for additional color temperatures.

** See page 2 for 347 volt options for Canada. 



POST TOP RETROFITS 360° OMNI DIRECTIONAL DESIGN



ORDERING GUIDE

PART #	UPC	REPLACES	WATTAGE	LUMENS	LPW	CCT (K)	BASE
LED-8033E30-A	844006081102	175W HID	35W	4239	121	3000K	E26
LED-8033E40-A	844006080570	175W HID	35W	5468	156	4000K	E26
LED-8033E57-A	844006081119	175W HID	35W	5617	160	5700K	E26
LED-8033M30-A	844006083328	175W HID	35W	4550	130	3000K	EX39
LED-8033M40-A	844006083342	175W HID	35W	5237	150	4000K	EX39
LED-8033M57-A	844006083366	175W HID	35W	5237	150	5700K	EX39
LED-8024E30-A	844006080341	250W HID	45W	6062	135	3000K	E26
LED-8024E40-A	844006080679	250W HID	45W	6924	154	4000K	E26
LED-8024E57-A	844006080242	250W HID	45W	6619	147	5700K	E26
LED-8024M30-A	844006080549	250W HID	45W	5893	131	3000K	EX39
LED-8024M40-A	844006080167	250W HID	45W	6930	154	4000K	EX39
LED-8024M57-A	844006080532	250W HID	45W	6632	147	5700K	EX39
LED-8046M30-A	844006081751	320W HID	65W	8450	130	3000K	EX39
LED-8046M40-A	844006081768	320W HID	65W	9587	147	4000K	EX39
LED-8046M57-A	844006081775	320W HID	65W	9499	146	5700K	EX39
LED-8027M30-A	844006080372	400W HID	100W	12486	125	3000K	EX39
LED-8027M40-A	844006080174	400W HID	100W	14666	147	4000K	EX39
LED-8027M57-A	844006080273	400W HID	100W	14613	146	5700K	EX39

347 VOLT OPTIONS FOR CANADA

PART #	UPC	REPLACES	WATTAGE	LUMENS	LPW	CCT (K)	BASE
LED-8033E30C-A	80844006081017	175W HID	35W	4740	135	3000K	E26
LED-8033E40C-A	80844006081024	175W HID	35W	5671	162	4000K	E26
LED-8033E57C-A	80844006081031	175W HID	35W	5537	158	5700K	E26
LED-8033M30C-A	80844006083332	175W HID	35W	4550	130	3000K	EX39
LED-8033M40C-A	80844006083356	175W HID	35W	5237	150	4000K	EX39
LED-8033M57C-A	80844006083370	175W HID	35W	5237	150	5700K	EX39
LED-8024E30C-A	80844006080775	250W HID	45W	5879	131	3000K	E26
LED-8024E40C-A	80844006080782	250W HID	45W	6600	147	4000K	E26
LED-8024E57C-A	80844006080799	250W HID	45W	6646	148	5700K	E26
LED-8024M30C-A	80844006080805	250W HID	45W	5856	130	3000K	EX39
LED-8024M40C-A	80844006080812	250W HID	45W	6740	150	4000K	EX39
LED-8024M57C-A	80844006080829	250W HID	45W	6818	152	5700K	EX39
LED-8046M30C-A	80844006081727	320W HID	65W	8471	130	3000K	EX39
LED-8046M40C-A	80844006081802	320W HID	65W	9619	148	4000K	EX39
LED-8046M57C-A	80844006081819	320W HID	65W	9440	145	5700K	EX39
LED-8027M30C-A	80844006080898	400W HID	100W	13304	133	3000K	EX39
LED-8027M40C-A	80844006080904	400W HID	100W	14736	147	4000K	EX39
LED-8027M57C-A	80844006080911	400W HID	100W	14349	143	5700K	EX39



Available from Major Electronix | sales@majorelectronix.com | 800-966-2345 | www.productsforautomation.com

09.19.18 Information is subject to change without notice.