




RP-B-LS LINEAR LED STRIP FIXTURE

RemPhosBASE



slim profile

flexCOLOR
switch on
each unit



- Ability to daisy chain multiple fixtures together.
- -OCC option comes with an integrated microwave sensor.
- Two installation options: suspended and surface mounted.
- flexCOLOR allows for a reduction in stocked skus.
- Great for schools, hospitals, grocery stores, offices and warehouses.
- Rated for damp enviroments.

flexCOLOR

choose from 3 different
color temperatures

flexCONTROL

order without controls,
with basic sensor, or advanced
Bluetooth mesh control

PART #	UPC	WATTAGE	LUMENS	LPW	CCT (K)**	Linear Ambient	Stairwell
						DLC CODE	DLC CODE
RP-B-LS-2FT-25L-840-FC	844006061258	20W	2670	137	3500/4000/5000K	PGUXC6L5	PO0C7Y78
RP-B-LS-2FT-25L-840-FC-OCC*	844006061265	20W	2670	137	3500/4000/5000K	PGUXC6L5	PO0C7Y78
RP-B-LS-4FT-40L-840-FC	844006061319	32W	4250	134	3500/4000/5000K	PIP65N0N	P6GRIQ3D
RP-B-LS-4FT-40L-840-FC-OCC*	844006061326	32W	4250	134	3500/4000/5000K	PIP65N0N	P6GRIQ3D

* 2FT set to 5000K = 140 LPW


Light Efficient Design
RemPhos

LIGHT EFFICIENT DESIGN HEADQUARTERS 188 S. Northwest Highway • Cary, IL 60013
INNOVATION & MANUFACTURING CENTER 30 Log Bridge Road, Building 200 • Middleton, MA 01949
847.380.3540 • led-llc.com


07.14.21 Information is subject to change without notice.



—○ PARTS & ACCESSORIES

SURFACE/CEILING MOUNT CONTINUOUS RUN BRACKETS


Use the surface/ceiling mount continuous run brackets to create strong and straight junctions between two fixtures.
Continuous run kits include: in-line Bracket, AC wiring, wire nuts.



PART #	UPC	DESCRIPTION
RP-B-LS-CR-SM-2FT	844006061432	2FT continuous run surface mount brackets
RP-B-LS-CR-SM-4FT	844006061449	4FT continuous run surface mount brackets

SUSPENDED MOUNT CONTINUOUS RUN BRACKETS


Use the suspended mount continuous run brackets to create strong and straight junctions between two suspended fixtures.
Continuous run suspended kits include: 4ft aircraft cable (2x), ceiling anchors, in-line Bracket, AC wiring, wire nuts.



PART #	UPC	DESCRIPTION
RP-B-LS-CR-SPND KIT-2	844006061463	2FT continuous run suspended mount brackets
RP-B-LS-CR-SPND KIT-4	844006061470	4FT continuous run suspended mount brackets

SUSPENDED KIT FOR SINGLE FIXTURE

Use the single fixture suspended kit to suspend one fixture from the ceiling.
Continuous run suspended kits include: 4ft aircraft cable (2x), ceiling anchors, in-line Bracket, AC wiring, wire nuts.



PART #	UPC	DESCRIPTION
RP-B-LS-SPND KIT-SINGLE-2-4	844006061418	2FT/4FT suspended kit for single fixture

—○ RP-B-LS IS ALSO COMPATIBLE WITH THE FOLLOWING SENSORS

- Standard Occupancy Sensor (-OCC)
- Limited Range Sensor (-OCCLR)
- Simple Grouping Sensor (-OCCRF)