



DESCRIPTION

4" Square Recessed LED With Integral Driver In Connection Box Available with Smooth & Baffle, White & Black Reflectors

FEATURES & BENEFITS

3 CCT User Selectable
CRI 90+ for True Color Rendering
Type IC Rated - No Housing Required
Fast & Easy To Install - Save On Labor

 $3\ensuremath{^{"}}$ Deep - Install Where Ceiling Space Is Limited

120V Triac Dimmable Driver with Wiring Compartment Included

REFLECTORS



4SR-SM-WH Smooth White



4SR-BF-WH Baffle White



4SR-SM-BK Smooth Black



4SR-BF-BK Baffle Black

ORDERING GUIDE

	Reflector	
JXL-COB04-S15W-CCT-	4SR-SM-WH	Smooth White
	4SR-SM-BK	Smooth Black
	4SR-BF-WH	Baffle White
	4SR-BF-BK	Baffle Black

White trim in stock. Black trim available as custom.


JXL-COB04-S15W-CCT


4" Square Recessed Economy LED 15W 3CCT

Project:	
Location:	
Reflector:	Qty:
Notes:	

SPECIFICATION		
Applications	Residential Recessed	
Energy Used	15 W	
Color Temperature (K)	3000 4000 5000	
Light Output WH Reflector (Im)	1200 1335 1290	
Light Output BK Reflector (lm)	1130 1305 1260	
Beam Angle	36°	
CRI	90 +	
Driver Input	120V AC 50/60 Hz	
J-Box Volume	7.4 in ³	
Dimming	TRIAC Dimmers 20% - 100%	
Approved Location	Insulated Ceiling & Damp Locations	
Air Tight	Yes	
Ambient Temperature	-4°F (-20°C) to +104°F (+40°C)	
Projected Life	70% Light Output at 30,000 Hours	
Certification	c ETL us	
Warranty	3 Year	

DIMENSIONS Fixture: Out SQ 4 3/4" In SQ 3 1/2" Depth 2 1/2"





Driver Dimensions 3 1/2" x 3 1/2" x 1 1/4"

ACCESSORIES Sold Separately



26" Long Flat Mounting Plate model # RIP4



13" Long Flat Mounting Plate model # MP4-2

Flanged Plate with Hanger Bars model # FRP4

Jumper Cable 10 ft model # JC-5CCT-10