



Type IC, Wet & Air-Tight

DESCRIPTION

2" Eyeball Round Recessed Gimbal LED With Integral Driver In Connection Box Unique & Patented Design: Gimbal Yet Air-Tight Without Housing Needed

FEATURES & BENEFITS


1 1/2" Deep - Install Where Ceiling Space Is Limited Type IC Rated - No Housing Required Fast & Easy To Install - Save On Labor Driver Inside Connection Box - No Junction Box Needed Directional Beam - Great for Sloped Ceilings and Artwork CRI 90+ for True Color Rendering

MOUNTING

Cut Hole In Ceiling And Snap Fixture In Opening With Attached Spring Clips Ceiling Clearance Required: 1 1/2" With Driver Remotely Installed

5" When Driver Is Next To The Fixture

DIMENSIONS: ID 2" OD 2 1/2" Cut Out 2" to 2 1/8"



Driver Included

Cable Rating FT4 / CMR



ORDERING GUIDE Example: LL2G - 30		K - WH	
	CCT	Trim Finish	
LL2G	-	-	
2700K	27K	WH	White
3000K	30K	BK	Black
4100K	41K	BN	Brushed Nickel

2" Eyeball Round Recessed Gimbal LED 5W

Project: Location: Qty: Cat #: Notes:

SPECIFICATION			
Applications	Cabinets, Recessed Alcoves		
Energy Used	5 W		
Color Temperature	2700 3000 4100		
Light Output	380 400 430		
Halogen Equivalent	35 W		
Beam Angle	24° Beam with 20° tilt and 360° rotation		
CRI	90 +		
Driver Input	120V AC 50/60 Hz		
Power Factor	0.95		
Dimming	TRIAC Dimmers 5% - 100%		
Approved Location	Insulated Ceiling & Wet Locations		
IP Rating	IP 54		
Air Tight	Yes		
Ambient Temperature	-40°F (-40°C) to +104°F (+40°C)		
Projected Life	70% Light Output at 50,000 Hours		
Certification	cULus Energy Star T24		
Warranty	10 Year on Residential		
vvaiianty	5 Year on Commercial Applications		

AVAILABLE TRIMS



ACCESSORIES Sold Separately



Low Volage Extension Cables 6ft - cat #EXC6, 20ft - cat #EXC20 Max 40 ft Allowed, FT4 / CMR rated



Rough-In Plates - cat #RIP2

COMPLIANCE









Type IC Air-Tight

USA Patent # US 10,344,952 B2 | Canada Patent # 2,967,954