



Lotus
LED
Lights



Type IC, Wet & Air-Tight

DESCRIPTION

3" Eyeball Round Recessed Gimbal LED
With Integral Driver In Connection Box
Unique & Patented Design:
Gimbal Yet Air-Tight Without Housing Needed


FEATURES & BENEFITS

1 3/4" Deep - Install Where Ceiling Space Is Limited
Type IC Rated - No Housing Required
Fast & Easy To Install - Save On Labor
Driver Inside Connection Box - No Junction Box Needed
Directional Beam - Great for Sloped Ceilings and Artwork
CRI 90+ for True Color Rendering

MOUNTING

Cut Hole In Ceiling And Snap Fixture In Opening
With Attached Spring Clips
Ceiling Clearance Required:
2 1/2" for Romex | 3 1/2" for MC or BX installations

DIMENSIONS: ID 2 1/2" OD 3 1/4" Cut Out 2 3/4" to 3"



120V TRIAC Dimmable Driver Included



Optional 120V-347V Driver 0-10V Dimmable



Order Separately as
Cat # LLL-LD0716T

ORDERING GUIDE Example: **LL3G - 30K - WH**

	CCT	Trim Finish	
LL3G	-	-	
2700K	27K	WH	White
3000K	30K	BK	Black
4000K	41K	BN	Brushed Nickel
Dim to Warm	32K	White Trim Only In Stock	
3000K to 2000K			

Lotus LED Lights USA

250 H Street # 301, Blaine WA 98230 tel 360-200-5500

Warehouses: Hainesport NJ, Naples FL, Dallas TX, Las Vegas NV, Lynnwood WA

www.LotusLEDLights.com

LL3G

3" Eyeball Round Recessed Gimbal LED 7.5W

Project:

Location:

Cat #:

Qty:

Notes:

SPECIFICATION	
Applications	Sloped Ceilings, Highlighting Artwork
Energy Used	7.5 W
Color Temperature	2700 3000 4100 DTW 30-20
Light Output	580 600 630 500
Halogen Equivalent	50 W
Beam Angle	38° Beam with 20° tilt and 360° rotation
CRI	90 +
Driver Input	120V AC Triac Dimmable
Power Factor	120V-347V AC 0-10V Dimmable
Dimming	0.95
Approved Location	Insulated Ceiling & Wet Locations
IP Rating	IP 54
Air Tight	Yes
Ambient Temperature	-40°F (-40°C) to +104°F (+40°C)
Projected Life	70% Light Output at 50,000 Hours
Certification	cULus, Energy Star (except DTW), T24
Warranty	10 Year on Residential 5 Year on Commercial Applications

AVAILABLE TRIMS



White



Black



Brushed Nickel

ACCESSORIES

Sold Separately



Low Voltage Extension Cables
6ft - cat # **EXC6**, 20ft - cat # **EXC20**
Max 40 ft Allowed. FT4 / CMR rated



Flat Rough-In Plates - cat # **RIP3**



Flanged Rough-In Plate - cat # **FRP3**



Goof Ring OD 4 1/2"
White cat # **GR3** Black cat # **GR3-BK**

COMPLIANCE



**Type IC
Air-Tight**

USA Patent # US 10,344,952 B2 | Canada Patent # 2,967,954

Lotus LED Lights CANADA

800-15355 24 Ave Box 200, Surrey BC V4A 2H9 tel 604-538-3090

Delta BC & Mississauga ON