



Type IC, Wet & Air-Tight

DESCRIPTION

2" Round Recessed Gimbal LED
With Integral Driver In Connection Box
Unique & Patented Design:
Gimbal Yet Air-Tight Without Housing Needed

FEATURES & BENEFITS


1 3/4" Deep - Install Where Ceiling Space Is Limited Type IC Rated - No Housing Required Fast & Easy To Install - Save On Labor Driver Inside Connection Box - No Junction Box Needed Directional Beam - Great for Sloped Ceilings and Artwork CRI 90+ for True Color Rendering

MOUNTING

Cut Hole In Ceiling And Snap Fixture In Opening With Attached Spring Clips Ceiling Clearance Required: 1 1/2" With Driver Remotely Installed

5" When Driver Is Next To The Fixture

DIMENSIONS: ID 2 1/2" OD 3" Cut Out 2 1/2" to 2 3/4"



Driver Included	Cable Rating F14 / CMI

ORDERING GUID	G GUIDE Example: LRG2 - 30K - WH		
	CCT	Trim Finish	
LRG2	-	-	
2700K	27K	WH	White
3000K	30K	BK	Black
4000K	40K		

2" Round Regressed Gimbal LED 5W

Project:

Location:

Cat #: Qty:

Notes:

SPECIFICATION		
Applications	Cabinets, Recessed Alcoves	
Energy Used	5 W	
Color Temperature	2700 3000 4000	
Light Output	380 400 430	
Halogen Equivalent	35 W	
Beam Angle	24° Beam with 20° tilt and 360° rotation	
CRI	90 +	
Driver Input	120V AC 50/60 Hz	
Power Factor	0.95	
Dimming	TRIAC Dimmers 5% - 100%	
Approved Location	Insulated Ceiling & Wet Locations	
IP Rating	IP 54	
Air Tight	Yes	
Ambient Temperature	-40°F (-40°C) to +104°F (+40°C)	
Projected Life	70% Light Output at 50,000 Hours	
Certification	cULus T24	
Warranty	10 Year on Residential	
	5 Year on Commercial Applications	

AVAILABLE TRIMS



White



Black

ACCESSORIES Sold Separately



Low Volage Extension Cables 6ft - cat #EXC6, 20ft - cat #EXC20 Max 40 ft Allowed. FT4 / CMR rated



Rough-In Plates - cat #RIP212

COMPLIANCE







Type IC Air-Tight

USA Patent # US 10,344,952 B2 | Canada Patent # 2,967,954

800-15355 24 Ave Box 200, Surrey BC V4A 2H9 tel 604-538-3090