Dimmers



- Toggle turns on/off
- Slide up to brighten, down to dim
- C•L® dimmers provide reliable dimming of dimmable CFLs/LEDs, as well as halogens and incandescents
- eco-dim_® model guarantees at least 15% energy savings and triples lamp life compared to a standard switch+

Incandescent/halogen dimmers



Dimmable LED bulbs (screw-base)

C•L preset dimmer

3-way/single-pole AYCL-153P-XX¹ 120 V 600 W (Inc.) 150 W (CFL or LED)

Visit www.lutron.com/dimcflled for an approved list of dimmable CFL/LED bulbs, and how to calculate wattage when mixing lamp types.

Preset dimmers

Single-pole	AY-600P- XX 1
120V 600W	7 th 6661 <u>242</u>
Single-pole	AY-10P- XX 1
120V 1000W	
3-way	AY-603P- XX 1
120V 600W	
3-way	AY-103P- XX 1
120V 1000W	

eco-dim preset dimmer†

3-way/single-pole	AY-603PG- XX 2
120V 600W	

▼ Magnetic low-voltage dimmers

Preset dimmers

Single-pole	AYLV-600P- XX 1
120V 600VA (450W)	
3-way	AYLV-603P- XX 1
120V 600VA (450W)	

The stated VA (Volt-Ampere) rating includes the magnetic transformer heat losses and the lamp load. The stated W (Watt) rating is the maximum lamp wattage based on assumed 20% transformer loss.

∠ 3-wire fluorescent dimmers*



Preset dimmers

3-way/single-pole	AYF-103P- XX 1
120V 8A	
3-way/single-pole	AYF-103P-277- XX 1
277V 6A	

For use with Hi-lume, Hi-lume 3D, and EcoSystem® ballasts, and Hi-lume A-Series LED drivers.

For more information on Hi-lume A-Series LED drivers, visit www.lutron.com/HilumeLED.

No derating required if ganged.

Adjustable low-end trim.

XX¹: Gloss color codes (except Gray), see pg. 106 **XX**²: Available in White (WH), Ivory (IV), Almond (AL) and Light Almond (LA), see pg. 106 (Wallplates not included. Order separately, see pg. 175)

All models must be derated if ganged unless otherwise noted, see pg. 179.

[†]Maximum light output of 85% guarantees 15% energy savings over standard switches.

*Requires neutral wire connection.