


PROJECT NAME:	CATALOG NUMBER:
	
NOTEC:	FIXTURE COUEDING.

Page: 1 of 2

LED PUCK LAMP

DRIVER ON BOARD, GEN 3 SERIES





















PRODUCT DESCRIPTION:

MaxLite's LED Puck Lamp is a leading edge energy efficient light source suitable for use in a wide variety of luminaires.

The puck lamp was designed with a proprietary heatsink which minimizes thermal levels allowing this light source to be used in totally enclosed luminaires.

FEATURES:

- Wattage: 10W Lumens: 800lm
- Efficacy (Im/W): 80
- Dimmability: Yes, Forward Phase Cut Dimmers
- Base: E26 & GU24 available
- Voltage: 120V only
- Operating Frequency: 50/60Hz
- Operating Temperature: -4°F-105°F
- Suitable for totally enclosed luminaires
- Integral LED Driver-on-Board engineering design
- Fits into same fixtures where Squat CFLs are used, allows cooler and longer-lasting fixture life
- · Light output equivalent to a 60W incandescent A-lamp
- Five year limited warranty
- Rated Lifetime: 25,000 hours

APPLICATIONS:

- Closet light
- · Ceiling fan
- Pendants
- Downlights
- Track lights
- · Coach lights
- Wall Sconces

ORDERING:

ORDER CODE	MODEL	WATTAGE	DIMMABLE	DELIVERED LUMENS	CRI	ENVIRONMENT RATED	сст	BASE TYPE	DIMENSIONS (MOL" x W")
103808	E10PUCD927/JA8	10W	Yes	800	92	Damp	2700K	E26	2.86" x 2.95"
103809	E10PUCD930/JA8						3000K		
103810	E10PUCGUD927/JA8						2700K	- GU24	2.26" x 2.95"
103812	E10PUCGUD930/JA8						3000K		

COMPATIBLE DIMMERS:

MAKE	DIMMER MODEL			
	S-600PR-WH			
Lutron	TGCL-153PH-WH			
	MACL-153MH-LA			
Leviton	WA-RXX-06674-12A			

NOTES:

- 1. This device is not intended for use with emergency exits
- See page 2 for compatible dimmer list





LED PUCK LAMP DRIVER ON BOARD, GEN 3 SERIES

Page: 2 of 2

SPECIFICATIONS:

ITEM	SPECIFICATION	DETAILS		
GENERAL PERFORMANCE	Power Consumption (W)	10		
	Efficacy (lm/W)	80		
	Lumens Delivered (Im)	800		
	Color Temperature	3000K		
	CRI	92		
	L70 Lifetime (hours)	25,000 Hrs		
ELECTRICAL	Input Voltage	120V		
	Power Factor	≥ 0.9		
PHYSICAL	Operating Temperature	-4°F to 105°F		
CERTIFICATION	Environment	Damp		
	Certification	cULus, LM-80		
	Material Usage	RoHS compliant; no mercury		
	Warranty	5 Years		