

TRADITIONAL FLUSH MOUNT LAMPS INCLUDED

ML2E242TR SERIES



Nickel



White



Dark Bronze



PRODUCT DESCRIPTION:

LED Flush Mount Ceiling Fixtures provide exceptional performance in general lighting applications for residential, multi-unit residential, hotels, and commercial properties. The series is available in nickel, white or bronze finishes with a high-transmission glass lens to complement virtually any décor. This bulb in a box solution comes prepackaged with JA8 compliant LED bulbs for ease of installation and guarantee of high CRI, flicker free LED performance

FEATURE:

- JA8 Lamp included - 2 x E12A19D927/JA8

DIMMING:

- 120V option available with 120V triac dimming (10%)

CONSTRUCTION:

- Die Form Steel housing
- Frosted glass lens
- Powder coat finish

LISTINGS:

- ETL listed for Damp Locations, Indoor
- ENERGY STAR Certified

WARRANTY:

5-year standard warranty* (further details available at www.maxlite.com/warranties)

*Product may be eligible for a warranty extension to 10 years, for an additional fee. Contact MaxLite for details.

ORDERING STRUCTURE:

MODEL SELECTION (Full list of order codes on pg. 2)						
ML2	E	242	TR			27
FAMILY	TYPE	SIZE	STYLE	FINISH	VOLTAGE	LAMP
ML2= Ceiling Flush Mounts	E= Edison Base E26	242= 2x11W Lamp	TR= Traditional	BZ= Dark Bronze NI= Nickel WH= White	[BLANK]= 120V, Triac dimming	27= 2700K, 90CRI, JA8

ORDERING:

ORDER CODE	MODEL NUMBER
103983	ML2E242TRNI27-V3
103984	ML2E242TRWH27-V3
103985	ML2E242TRBZ27-V3

DIMMING COMPATIBILITY:

BRAND	DIMMER MODELS
LUTRON	YCL-153P-WH, AYCL-153PH, DVCL-153P-WH, DVWCL-153PH-WHC, S-603PH-WH, SCL-153PH-WH, TGCL-153PH-WH
LEVITON	6631, 6672, 6683, 603-6631-A, 6631-A, 6683-10Z, IPI06-1LZ, IPI10-1LZ, IPL06

SPECIFICATIONS:

ML2E242xxxxxx-V3	
SPECIFICATION	DETAILS
Nominal Wattage (W)	24W
Source Lumens (lm)	2200 lm
Delivered Lumens (lm)	1593 lm
Efficacy (lm/W)	75
Equivalency	2 x 75W Inc.
CRI	≥90
Color Temperature	2700K
Lumen Maintenance (L70)	≥25,000 hours
Voltage	120V, Triac Dimming , 10%
Power Factor	≥0.90
Housing	Die Form Steel metal
Lens	Frosted Glass
Mounting	Ceiling
Operating Temperature	0°F - 104°F
Listings	ENERGY STAR, TITLE 24, cETLus, FCC
Environment	Damp locations, Indoor
Warranty	5 Year

PRODUCT DIMENSIONS:

