

PROJECT NAME: _____
 NOTES: _____

CAT. #: _____
 FIXTURE SCHEDULE: _____

Slim Downlight Baffle Style

SDB Series



Description:

The CCT Selectable Slim Downlights mount directly into the ceiling, requiring no can. With a simple flick of a switch on the remote driver junction box, installers can choose from 2700K, 3000K, 3500K, 4000K or 5000K as CCT to suit various application needs. Low profile and easy to install, the Flush style fixture is Energy Star, Wet locations, IC rated and supports Title 24. Its edge lit optics provide an even and low glare illumination with an outstanding color rendering, making it the ideal choice for hospitality, retail, offices and multi-unit residential spaces.

Features:

- 2700K/ 3000K/3500K/4000K/5000K CCT Selectable
- CRI: ≥90
- Beam angle: ~110°
- IC Rated
- Mounts into ceiling without the use of a separate housing
- Field installable Emergency Battery back up kit available (includes a test switch and the charge indicator kit, no cover)

Dimming:

- 120V option available with 120V triac dimming

Construction:

- Die cast Aluminum housing
- Plastic Lens

Listings:

- ETL Listed for wet locations
- ENERGY STAR certified
- IC rated
- Airtight construction
- Supports T24 Part 6 high efficacy lighting requirements

Ordering Information

FAMILY	SHAPE	SIZE	WATTAGE (NOMINAL)	CRI+ COLOR SELECTABLE	TRIM
SDB= Slim Downlights Baffle style	R= Round	4= 4"	12= 12W	9CS= 90 CRI, 2700/3000/3500/4000/5000 (Default is 3000K)	W= White
		6= 6"			
		8= 8"	18= 18W		

Stocked Items

ORDER CODE	MODEL NUMBER	ENERGY STAR #
105304	SDBR4129CSW	2371978
105361	SDBR6129CSW	2371979
105306	SDBR8189CSW	2371981

Accessories

ORDER CODE	MODEL NUMBER	DESCRIPTION	IMAGE
14098874	RCF-4	4" Commercial Recessed Frame, New Construction	
14098875	RCF-6	6" Commercial Recessed Frame New Construction	
14098876	RCF-8	8" Commercial Recessed Frame, New Construction	
100298	EBUUP15007N0100	Emergency Battery Back up, 07W, 100-347V, Field installable	



5-year standard warranty* (see terms at www.maxlite.com/warranties)

*Excludes EM/MS versions; component warranty applies. *Product may be eligible for warranty extension to 10 years for an additional fee. Limitations apply, contact MaxLite for details.

Slim Downlight Baffle Style

SDB Series

Dimming Compatibility

DIMMER MODELS	
Lutron	DVCL-153PR-WH, CTCL-153PDH-WH, TGCL-153PH-WH, MACL-153MH-WH, P-PKG1W-WH-R
Leviton	R62-06674-P0W, R12-06672-1LW, R50-IPL06-10M
Eaton	AAL06-C1, SAL06P-LA-K

Specifications

	SDBR4129CSW	SDBR6129CSW	SDBR8189CSW
Power Consumption	12W	12W	18W
Equivalency	75W INC	75W INC	125W INC
Lumens Delivered	800 lm	900 lm	1500 lm
Lumens Battery Mode	750 lm	850 lm	1350 lm
Efficacy	67 lm/w	75 lm/w	83 lm/w
Beam Angle	~100°		
CRI	≥ 90		
Color Temperature (K)	2700K/3000K/3500K/4000K/5000K (Default is 3000K)		
L70 Lumen maintenance	≥ 50,000		
Power Factor	≥ 0.9		
Input Voltage	120V, 60Hz		
Dimming	Triac Dimming Range: 10%-100%		
Operating Temperature	-4°F TO 104°F (-20°C TO 40°C)		
Listings	cETLus, FCC, Title 24 Compliant, JA8, IC Rated, Airtight		
Environment	UL listed for Wet location		
Warranty	5 Year Warranty		

Dimensions:

