

Version	2.0	Date	8/17/23
Prepared By	JC		

PRODUCT SPECIFICATION			
Category	Slim Area Light		
Item Number	9610		
Stock Code	FXSAL240SW/840/BZ/T3		
Mounting	Pole Mount/ Slip Fitter/ Yoke Mount/ Wall Mount		
Housing Color	Bronze (RAL#8019)		



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	160 / 190 / 240	Replacement Wattage (W)	400-100
Tested Wattage (W)	-		
Input Voltage (V)	120-277		
Voltage Frequency (Hz)	50/60	Surge Protect Level	10KV
Input Current (A)	2.18	Dimmable	0-10V
Power Factor	>0.9	AUX (12V) Line	Yes
THD	<20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	22,400 / 26,600 / 34,829	CCT (K)	4000K
Efficacy (lm/w)	145	Beam Angle (°)	Type 3
CRI	>80		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	- 40°F ~ 122°
Storage Temperature (°F)	- 40°F ~ 140°F
IP Rating	IP66
IK Rating	IK08
Rated Life (Hrs)	50,000
Warranty (Yrs)	7

ACCESSORIES		
Item #	Stock Code	Description
P10453	MT-AL/PM6/BZ	6" Pole Mount Arm
P10455	MT-AL/SF/BZ	Slip Fitter
P10473	MT-AL/WM/BZ	Wall Mount
P10456	MT-SAL/YK12/BZ	12" Yoke Mount

PRODUCT DIMENSIONS		
Width- in / (mm)	12.01"	307
Height- in / (mm)	2.67"	68
Depth- in / (mm)	21.65"	550
EPA (ft²)	0.25 ft² (@ 0 deg)	
Weight (lbs)	15.5	
Mounting Height (ft)	20~40	
Cable Length (ft)	1.64	

Technical drawings of the Slim Area Light showing front, side, and rear views with dimensions:

- Front view: Shows the light fixture with a width of 12.01in (307mm) and a height of 2.67in (68mm).
- Side view: Shows the light fixture with a depth of 21.65in (550mm).
- Rear view: Shows the mounting bracket with a width of 12.01in (307mm) and a height of 2.67in (68mm).

CERTIFICATIONS			
UL/ETL	ETL/cETL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	5.1 Premium	RoHS	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS