

natural^{led}

Product Engineering Spec

Product Spec			
Category	LED Wall Pack	PICTURE	
Item Code	9449		
Stock Code	FXTWP60/40K/BZ-PHO		
Mounting	Wall Mount		
Housing Color	Bronze		

Electric Characteristics		Photometric Characteristics	
Rated Wattage (W)	60	Lumen (lm)	9000
Tested Wattage (W)	60	Efficacy (lm/w)	150
Input Voltage (V)	120~277	CRI	80
Voltage Frequency (Hz)	50/60	CCT (K)	4000
Input Current (A)	0.5 (@120V)	Beam Angle (°)	Forward Throw
Power Factor	>0.9	General Characteristics	
Replacement Wattage (W)	250~400	Operating Temperature	-22°F~122°F
Surge protect level	4KV	Storage Temperature	-40°F~140°F
Dimmable	0-10V	IP rating	IP65
THD	<20%	Rated Life	50000 hrs
		Warranty	5 years

Product Dimensions		Suggested Accessory	
Weight (lbs.)	6.86	120~277 AC EM driver - Item# 7334	
Height (in)	9.16	Microwave Sensor - Item# P10234	
Depth	7.51	Wireguard - Item# P10004	
Width (in)	14.29		
Mounting Height (ft)			
Cable Length (ft)			

Qualifications			
UL/ETL	ETL/cETL	LM79	✓
Energy Star		LM80	✓
DLC	V5.1 Premium	IES File	✓
CEC		FDA	
JA8		NEMA	
FCC	✓	Dimmer List	
RoHS	✓		

Comments:

Photocell Included with Fixture