

|             |     |      |         |
|-------------|-----|------|---------|
| Version     | 2.0 | Date | 7/20/18 |
| Prepared By | JC  |      |         |

| PRODUCT SPECIFICATION |                     |         |                                                                                     |
|-----------------------|---------------------|---------|-------------------------------------------------------------------------------------|
| Category              | LED Lamp            | PICTURE |  |
| Item Number           | 5907                |         |                                                                                     |
| Stock Code            | LED12PAR38/110L/930 |         |                                                                                     |
| Mounting              | E26                 |         |                                                                                     |
| Housing Color         | White               |         |                                                                                     |

| ELECTRICAL CHARACTERISTICS |       |                         |     |
|----------------------------|-------|-------------------------|-----|
| Rated Wattage (W)          | 12    | Replacement Wattage (W) | 90  |
| Tested Wattage (W)         | 12    |                         |     |
| Input Voltage (V)          | 120   | Surge Protect Level     | -   |
| Voltage Frequency (Hz)     | 50/60 |                         |     |
| Input Current (A)          | -     | Dimmable                | Yes |
| Power Factor               | >0.9  | AUX (12V) Line          | -   |
| THD                        | -     |                         |     |

| PHOTOMETRIC CHARACTERISTICS |       |                |       |
|-----------------------------|-------|----------------|-------|
| Lumen (lm)                  | 1,050 | CCT (K)        | 3000K |
| Efficacy (lm/w)             | 88    | Beam Angle (°) | 40°   |
| CRI                         | 90    |                |       |

| GENERAL CHARACTERISTICS    |               |
|----------------------------|---------------|
| Operating Temperature (°F) | -4°F ~ 104°   |
| Storage Temperature (°F)   | -4°F ~ 140°   |
| IP Rating                  | Damp Location |
| IK Rating                  | -             |
| Rated Life (Hrs)           | 25,000        |
| Warranty (Yrs)             | 3             |

| ACCESSORIES |            |             |
|-------------|------------|-------------|
| Item #      | Stock Code | Description |
|             |            |             |
|             |            |             |
|             |            |             |
|             |            |             |
|             |            |             |

| PRODUCT DIMENSIONS   |   |   |  |
|----------------------|---|---|--|
| Width- in / (mm)     | - | - |  |
| Height- in / (mm)    | - | - |  |
| Depth- in / (mm)     | - | - |  |
| IK Rating            | - |   |  |
| Weight (lbs)         | - |   |  |
| Mounting Height (ft) | - |   |  |
| Cable Length (ft)    | - |   |  |

| CERTIFICATIONS     |    |      |   |
|--------------------|----|------|---|
| UL/ETL             | UL | CEC  |   |
| NSF/ETL Sanitation |    | JA8  |   |
| Energy Star        | ✓  | FCC  | ✓ |
| DLC                |    | RoHS | ✓ |

| DOCUMENTS |   |             |   |
|-----------|---|-------------|---|
| LM79      | ✓ | IES File    | ✓ |
| LM80      | ✓ | Dimmer List |   |
|           |   |             |   |
|           |   |             |   |

| COMMENTS |
|----------|
|          |