

NJCB-09

9W Driver Box for 1" Iolite Can-less and 2" M-Wave Can-less Downlights

Type
Project
Catalog No.
Notes

PRODUCT DESCRIPTION

IC rated driver box with dimmable driver. Used in conjunction with 1" Iolite Can-less LED modules or 2" M-Wave Can-less downlights.

FEATURES

- No housing required - IC Air-Tight rated
- Easy installation for remodel or new construction applications
- Compatible with 1" Iolite Can-less or 2" M-Wave Can-less downlights
- Quick disconnect allows for extended lengths with accessories
- IC rated
- 120VAC input
- Triac or ELV dimming
- JA8-2022, cULus and ENERGY STAR qualified
- cULus Listed for Wet Locations (when used with compatible module/trim)

SPECIFICATION

Construction: Prewired junction box includes 7" quick connect wire to the LED module for ease of installation. Junction box includes two 1/2" trade size knockouts and snap on cover.

Clearance: IC rated driver boxes can be installed with direct contact against insulation (not spray foam insulation), no minimum clearance is required.

Installation: Can be used in remodel applications without any additional frame. Can be used in new construction applications with universal new construction frame-in ([NF-R124](#)).

ELECTRICAL

Input Voltage: 120VAC

Wattage: 9W

Operating Temperature: 0°-30°C

Dimming: Triac or ELV

COMPATIBLE LUMINAIRES

Driver box is compatible with 1" Iolite Can-less and 2" M-Wave Can-less downlights

Iolite Can-less

[NI0C-1LED](#) 1" Iolite Can-less LED Module

M-Wave Can-less

[NMW-2LED](#) 2" M-Wave LED Module

OPTIONAL ACCESSORIES

[NF-R124](#): Universal New Construction Frame-In

[NCA-EW-4](#): 4' Quick Connect Extension Cable


[NCA-EW-10](#): 10' Quick Connect Extension Cable

LABELS AND LISTINGS

- cULus Listed for Damp Locations (Wet Location when used with compatible module/trim)
- ENERGY STAR certified (when used with compatible module/trim)
- [5-Year Limited Warranty](#)
- Certified to the high efficacy requirements of California Title 24 JA8-2022 (when used with compatible module/trim)



PRODUCT IMAGES & DIMENSIONS



NF-R124

Universal New Construction Frame-In



NCA-EW

Quick Connect Extension Cable

9W Driver Box

Wattage / Input Voltage / Dimming

NJCB-09 = 9W / 120VAC input / Triac or ELV dimming

Optional Accessories

Description

NF-R124 = Universal New Construction Frame-In

NCA-EW-4 = 4' Quick Connect Extension Cable

NCA-EW-10 = 10' Quick Connect Extension Cable

Example: **NJCB-09** = 9W Driver Box with 120VAC input; Triac or ELV dimming