

NL-3420

3" Square Trim with 1-1/2" Pinhole

Source: 50W max.
MR16

PRODUCT IMAGES AND DIMENSIONS



CONSTRUCTION

Trim: 3" die-cast aluminum flange provides sharp clean corners. Gimbal ring allows lamp to be mounted on top of the reflector and adjustable up to 35°.

Mounting: Trim includes three trim clips that securely mounts inside the housing.

COMPATIBLE LAMP / HOUSINGS

Line Voltage:

10W MR16 GU10 max. (NHIC-350AT/10; NH-350AT/10; NHR-354AT/10)

20W MR16 GU10 max. (NHIC-350AT/20; NH-350AT/20; NHR-354AT/20)

50W MR16 GU10 max. (NHIC-350AT; NH-350AT; NHR-354AT)

Low Voltage:

3-50W MR16 LED (NLIC-301AT/1EL; NL-301AT/1EL; NLR-304AT/1EL)

20W MR16 max. (NLIC-301QAT/20; NL-301QAT/20; NLR-304QAT/20; NLR-305AT/20)

37W MR16 max. (NLIC-301QAT/37; NL-301QAT/37; NLR-304QAT/37; NLR-305AT/37)

50W MR16 max. (NLIC-301QAT; NLIC-301AT/1EL; NL-301QAT; NL-301AT/1EL; NLR-304QAT; NLR-304AT/1EL; NLR-305AT)

LISTING

cULus Listed for damp locations when used with compatible housing



Compatible Housings

Item Number / Description / Max. Wattage

LINE VOLTAGE

NHIC-350AT/10 = IC Air-Tight New Construction / 10W

NHIC-350AT/20 = IC Air-Tight New Construction / 20W

NHIC-350AT = IC Air-Tight New Construction / 50W

NH-350AT/10 = Non-IC Air-Tight New Construction / 10W

NH-350AT/20 = Non-IC Air-Tight New Construction / 20W

NH-350AT = Non-IC Air-Tight Remodel / 50W

NHR-354AT/10 = Non-IC Air-Tight Remodel / 10W

NHR-354AT/20 = Non-IC Air-Tight Remodel / 20W

NHR-354AT = Non-IC Air-Tight Remodel / 50W

LOW VOLTAGE

NLIC-301QAT/20 = ICAT New Construction / 120V Magnetic / 20W

NLIC-301QAT/37 = ICAT New Construction / 120V Magnetic / 37W

NLIC-301QAT = ICAT New Construction / 120V Magnetic / 50W

NLIC-301AT/1EL = ICAT New Construction / 120V Electronic / 50W

NL-301QAT/20 = Non-IC AT New Construction / 120V Magnetic / 20W

NL-301QAT/37 = Non-IC AT New Construction / 120V Magnetic / 37W

NL-301QAT = Non-IC AT New Construction / 120V Magnetic / 50W

NL-301AT/1EL = Non-IC AT New Construction / 120V Electronic / 50W

NLR-304QAT/20 = Non-IC AT Remodel / 120V Magnetic / 20W

NLR-304QAT/37 = Non-IC AT Remodel / 120V Magnetic / 37W

NLR-304QAT = Non-IC AT Remodel / 120V Magnetic / 50W

NLR-304AT/1EL = Non-IC AT Remodel / 120V Electronic / 50W

NLR-305AT/20 = Non-IC AT Remodel / No Transformer / 20W

NLR-305AT/37 = Non-IC AT Remodel / No Transformer / 37W

NLR-305AT = Non-IC AT Remodel / No Transformer / 50W

3" Square Trim with 1-1/2" Pinhole - Housing Required

Series	Finish
NL-3420 = 3" Square Trim with 1-1/2" Pinhole	BB = Black Interior / Black Trim
	BW = Black Interior / White Trim
	BZBZ = Bronze Interior / Bronze Trim
	NN = Natural Metal Interior / Natural Metal Trim
	WW = White Interior / White Trim

Example: **NL-3420WW** = 4" Square White Trim with White Pinhole