

# NLOPAC-R4T24

## 4" AC T24 Opal - LED Surface Mount

Source: 13W LED  
850lm

Type

Project

Catalog No.

Notes

### PRODUCT DESCRIPTION

The AC Opal LED Series LED fixture is designed to surface mount over a standard junction box. The low profile dimmable luminaire produces even illumination and is cULus listed for wet locations.

### FEATURES

- AC LED (No Driver)
- Dimmable
- 2700K, 3000K or 4000K @ 90+ CRI
- Mount on standard 4" junction box
- ENERGY STAR certified

### SPECIFICATION

**Construction:** One piece aluminum die formed housing and trim. Aluminum body dissipates heat and extends life.

**Mounting:** AC Opal (no driver) is flat on the back and suitable for installation on most 4" octagon boxes or 4/0 plaster ring. Luminaires can be installed in covered ceiling and wall mount.

**Optics:** Nora specified and designed precision molded lens for optimal lumen output and even distribution.

**Ratings:** IC rated when used with a 4" electrical junction box rated for direct contact with insulation. Fire rated when used with a fire rated junction box.

### ELECTRICAL

**Input Voltage:** 120V

**Operating temperature:** 0-45°C

**Lumens / Wattage:** 850lm / 13W

**Color Temperature:** 2700K, 3000K, 4000K

**CRI:** 90+

**Dimming:** 5% with Triac or 10% with ELV

[Click Here](#) or check complete dimmer list at [www.NoraLighting.com](http://www.NoraLighting.com) in the "Compatibility" page under "Resources" tab

### ACCESSORIES


**NLOPAC-4BKT-2:** Universal bracket for mounting to 3" or 4" junction boxes.

### LISTING

- cULus Listed for wet locations (covered ceiling only)
- ENERGY STAR certified
- [5-Year Limited Warranty](#)
- RoHS Compliant
- Certified to the high efficacy requirements of California Title 24 JA8-2019
- Suitable for use in closets when installed in accordance to NEC Section 410.16 (A)(1) and 410.16 (C)(1).



### PRODUCT IMAGES AND DIMENSIONS



**BZ**  
Bronze



**NM**  
Natural Metal



**W**  
White



**NLOPAC-4BKT-2**  
Universal Bracket for 3" or 4" Junction Boxes

## 4" AC T24 Opal - LED Surface Mount

Color Temperature / Finish

**NLOPAC-R4T2427BZ** = 2700K / Bronze

**NLOPAC-R4T2427NM** = 2700K / Natural Metal (Discontinued, direct replacement: [NLOPAC-R4509T2427NM](#))

**NLOPAC-R4T2427W** = 2700K / White (Discontinued, direct replacement: [NLOPAC-R4509T2427W](#))

**NLOPAC-R4T2430BZ** = 3000K / Bronze (Discontinued, direct replacement: [NLOPAC-R4509T2430BZ](#))

**NLOPAC-R4T2430NM** = 3000K / Natural Metal

**NLOPAC-R4T2430W** = 3000K / White

**NLOPAC-R4T2440BZ** = 4000K / Bronze

**NLOPAC-R4T2440NM** = 4000K / Natural Metal (Discontinued, direct replacement: [NLOPAC-R4509T2440NM](#))

**NLOPAC-R4T2440W** = 4000K / White

## Optional Accessories

Description

**NLOPAC-4BKT-2** = Universal Bracket for 3" or 4" Junction Boxes

Example: **NLOPAC-R4T2430W** = 4" AC T24 Opal, 850lm / 13W, 3000K, White finish