

# NMP2-LED

## 24V Josh LED Puck Light

Source: 3.5W LED  
300lm

Type

Project

Catalog No.

Notes

### PRODUCT DESCRIPTION

Josh, a slim light disk LED system for accent, under cabinet, in-cabinet, niche, and jewelry cases, and other applications with limited space. These low-profile fixtures can be spaced together to provide excellent and even illumination on all surfaces. The Josh pucks does not produce a diode image and can be recessed or surface mounted. Combined with ultra low-profile housing, Josh offers unique features and a great ease of installation. LED technology eliminates forward heat from the fixture, also no UV or infrared rays to harm artwork, retail displays or heat sensitive foods. The luminaire produces more light than a traditional 20 watt xenon or halogen puck while consuming only 3.5 watts each puck.

### FEATURES

- 24V Low Voltage System
- 300lm / 3.5W
- 2700K, 3000K, 3500K or 4000K @ 90+ CRI
- Well suited for very small spaces 0.6" deep with 2.72" diameter
- Recessed or surface mount
- Easy installation
- Dimmable with power supply
- 12", 24", 38" and 48" extension cables accessory available.
- No flicker delay or warm up like compact fluorescent products
- No UV light or infrared wavelengths
- 5-Year Limited Warranty
- Each puck comes with a 72" wire and connector

### ELECTRICAL

**Input Voltage:** 24VDC

**Lumens / Wattage:** 300lm / 3.5W

**Color Temperature:** 2700K, 3000K, 3500K, 4000K

**Color Rendering Index:** 90+ CRI

**Operating Temp.:** 20°C to 50°C

**Cord Length:** 72" wire and connector

**Maximum # of Units Per Interconnect:** Six luminaires can be connected to interconnect (NMPA-6P-24). Each luminaire must connect to interconnect, cannot daisy chain.

**Life Expectancy:** 50,000 hours

**Dimming:** Specified by driver

**Cabinet Installation:** Up to three puck lights may be installed in an enclosed cabinet size of 3.5" x 11.5" x 12"

### LABELS AND LISTINGS

- cULus Listed for Damp Location
- cULus Listed for under-cabinet and cabinet use
- 5-Year Limited Warranty
- RoHS compliant



### Performance Data

Part Number	Lumens	CCT
<b>NMP2-LED27</b>	282lm	2700K
<b>NMP2-LED30</b>	302lm	3000K
<b>NMP2-LED35</b>	297lm	3500K
<b>NMP2-LED40</b>	307lm	4000K

### PRODUCT IMAGES AND DIMENSIONS



Black



Bronze




Brushed Nickel



White

#### Recessed Mount



0.06"


Cut out: 2.5" (without mounting bracket)  
2.74" (with mounting bracket)

#### Surface Mount



0.57"

2.72"



1.63"

## 24V Josh LED Puck Light

Catalog No.:	Color Temp.	Finish
<b>NMP2-LED</b>	<b>27</b> = 2700K	<b>B</b> = Black
	<b>30</b> = 3000K	<b>BZ</b> = Bronze
	<b>35</b> = 3500K	<b>BN</b> = Brushed Nickel
	<b>40</b> = 4000K	<b>W</b> = White

Example: **NMP2-LED30B** = 24V Josh LED Puck Light, 3000K, Black Finish

# NMP2-LED

## 24V Josh LED Puck Light Accessories

Type
Project
Catalog No.
Notes



6-Port Power Line Interconnect

<b>NMPA-6P-24B</b>	Black
<b>NMPA-6P-24W</b>	White

Terminal block connects up to six LED Josh Puck lights to a Nora driver. Includes 24" cord with RCA jack.



Extension Cable

<b>NMPA-EW-12</b>	12"
<b>NMPA-EW-24</b>	24"
<b>NMPA-EW-36</b>	36"
<b>NMPA-EW-48</b>	48"

Finish: Black (B), White (W)

Used to extend the length of the cable from the puck to the terminal block. Linkable up to 110".



2' Wire Raceway

<b>NATL-422B</b>	Black
<b>NATL-422W</b>	White

Field-cutable plastic. Includes wire channel with double faced tape and cover.



In-Line Touch Dimmer

<b>NATL-518W</b>
------------------

72W max., no power fail memory, touch on/off and hold to dim.



Direct Plug-In LED Driver

<b>NATL-524W</b>	24V 24W
<b>NATL-545W</b>	24V 45W

**Input Voltage:** 120V  
**Cable Length:** 6'



Direct Plug-In LED Driver

<b>NATL-596W</b>	24V 96W
------------------	---------

**Input Voltage:** 120V  
**Input Wire:** 44" Cord and Plug  
**Output Wire:** 58" Power line connector



Class II Hardwire LED Driver

<b>NATL-5100HW</b>	24V 81.6W
--------------------	-----------

**Input Voltage:** 120-240V  
**Dimming:** Non-Dimmable  
**Includes:** 10' Power Line Connector



Class II Hardwire LED Driver  
0-10V Dimming

<b>NATL-5096-24-HWD10</b>	24V 81.6W
---------------------------	-----------

**Input Voltage:** 120-277V  
**Dimming:** 0-10V  
**Includes:** 10' Power Line Connector



Class II Hardwire LED Driver  
ELV Dimming

<b>NATLED-5040HW</b>	24V 40W
----------------------	---------

**Input Voltage:** 120V  
**Dimming:** ELV  
**Includes:** 10' Power Line Connector



Class II Hardwire LED Driver with Regulator, MLV Dimming

<b>NMTD-60/24D</b>	24V 60W
<b>NMTD-96/24D</b>	24V 96W

**Input Voltage:** 120-277V  
**Dimming:** Magnetic Low Voltage Regulator: Integral regulator for constant current and voltage  
**Includes:** 10' Power Line Connector



Power Line Connector

<b>NALTL-10</b>	10' Power Line
<b>NALTL-30</b>	30' Power Line

For use with Class II drivers. Carries output from driver, requires power line interconnectors.

<b>NATL-302W</b>	5" Splitter
------------------	-------------

Splits power line connector into two separate leads, requires power line cable.



Low Voltage Splice Box

<b>NATL-415W</b>
------------------

Use to join low voltage lead to low voltage power line connector or interconnector.



16AWG In-Wall Rated Wire

<b>NATL-W16-2-250</b>	250'
<b>NATL-W16-2-20</b>	20'

16 AWG low voltage Class II two-conductor, in-wall rated wire.



Wire Clip, Plastic - 10pk

<b>NATL-404W</b>	J-Clip
<b>NATL-405W</b>	Over the Wire
<b>NATL-406W</b>	Square Clip

# NMP2-LED Sample Layout


24V Josh LED Puck Light

Type \_\_\_\_\_


Project \_\_\_\_\_

Catalog No. \_\_\_\_\_

Notes \_\_\_\_\_



A	<b>NATL-545W</b>	24V 45W Direct Plug-In Driver
A2	<b>NMTD-60/24D</b>	24V 60W Dimmable Class II Power Supply
B	<b>NALTL-10</b>	10' Power Line Connector
C	<b>NMPA-6P-24</b>	Power Line Interconnect with 6-port terminal block
D	<b>NMPA-EW-12B/W</b> <b>NMPA-EW-24B/W</b> <b>NMPA-EW-36B/W</b> <b>NMPA-EW-48B/W</b>	12" Extension Cable 24" Extension Cable 36" Extension Cable 48" Extension Cable
E	<b>NMP2-LED</b>	24V Josh LED Puck Light



# PHOTOMETRICS

## 24V Josh LED Puck Light

Type


Project

Catalog No.

Notes

### Test Information

Test Number: NTS182R1  
 Part Number: NMP2-LED27W  
 Beam Spread: 113° Wide Flood  
 Lumens: 282lm  
 Wattage: 5.27W  
 Efficacy: 54lpw  
 CCT / CRI: 2700K / 90 CRI  
 Spacing Criteria (0°-180°): 1.26  
 Spacing Criteria (90°-270°): 1.26



### Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	6.1fc	12"-2"
6'	2.7fc	18"-4"
8'	1.5fc	24"-5"
10'	1.0fc	30"-6"
12'	0.7fc	36"-7"

### Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	76	27.0
0-40	125	44.2
0-60	221	78.4
0-90	282	100
90-180	0	0
0-180	282	100

### Candela Table

Vertical Angles	Candela
0	98
5	98
15	94
25	88
35	78
45	66

### Test Information

Test Number: NTS183R1  
 Part Number: NMP2-LED30W  
 Beam Spread: 113° Wide Flood  
 Lumens: 302lm  
 Wattage: 5.42W  
 Efficacy: 56lpw  
 CCT / CRI: 3000K / 90 CRI  
 Spacing Criteria (0°-180°): 1.26  
 Spacing Criteria (90°-270°): 1.26



### Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	6.6fc	12"-2"
6'	2.9fc	18"-4"
8'	1.6fc	24"-5"
10'	1.0fc	30"-6"
12'	0.7fc	36"-7"

### Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	82	27
0-40	134	44.2
0-60	237	78.4
0-90	302	100
90-180	0	0
0-180	302	100

### Candela Table

Vertical Angles	Candela
0	105
5	105
15	101
25	94
35	83
45	70

### Test Information

Test Number: NTS184R1  
 Part Number: NMP2-LED35W  
 Beam Spread: 113° Wide Flood  
 Lumens: 297lm  
 Wattage: 5.2W  
 Efficacy: 57lpw  
 CCT / CRI: 3500K / 90 CRI  
 Spacing Criteria (0°-180°): 1.26  
 Spacing Criteria (90°-270°): 1.26



### Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	6.5fc	12"-2"
6'	2.9fc	18"-4"
8'	1.6fc	24"-5"
10'	1.0fc	30"-6"
12'	0.7fc	36"-7"

### Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	80	27
0-40	131	44.2
0-60	233	78.4
0-90	297	100
90-180	0	0
0-180	297	100

### Candela Table

Vertical Angles	Candela
0	103
5	103
15	102
25	93
35	82
45	69

### Test Information

Test Number: NTS185R1  
 Part Number: NMP2-LED40W  
 Beam Spread: 113° Wide Flood  
 Lumens: 307lm  
 Wattage: 5.19W  
 Efficacy: 59lpw  
 CCT / CRI: 4000K / 90 CRI  
 Spacing Criteria (0°-180°): 1.26  
 Spacing Criteria (90°-270°): 1.26



### Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	6.7fc	12"-2"
6'	3.0fc	18"-4"
8'	1.7fc	24"-5"
10'	1.1fc	30"-6"
12'	0.7fc	36"-7"

### Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	83	27
0-40	136	44.2
0-60	241	78.4
0-90	307	100
90-180	0	0
0-180	307	100

### Candela Table

Vertical Angles	Candela
0	107
5	107
15	103
25	96
35	85
45	71