

NUTP6 Series
12V RGB Color Changing LED Tape Light
Source: 2.5W/ft. LED

Type
Project
Catalog No.
Notes

PRODUCT DESCRIPTION

RGB LED Tape Light has the colors Red, Green, and Blue in every LED diode. Several colors of visual spectrum can be selected and programmed with a 120° viewing angle. A stationary color, automatic changing colors and brightness can be selected and changed at anytime with the press of a button. This flexible LED light source is a durable silicone encapsulated tape, cULus Listed for Damp Location applications.

FEATURES

- Available in 16' roll, 12" section, and 6" section
- Separable every 12", easily disconnected and connected without soldering
- Field cuttable every 6" or 6 LEDs
- 120° Beam Angle
- Easy to install; pre-applied 3M™ tape or 15 acrylic mounting clips (included with roll)
- Primary Colors: Red, Green, and Blue
- cULus Listed for Damp Location
- No soldering or additional wiring is required
- No flicker delay or warm up like compact fluorescent products
- No UV light or infrared wavelengths
- 3-Year Limited Warranty

INCLUDED WITH EVERY 16' ROLL

(1) 16' Tape Light Roll with 12" separable sections, (15) Acrylic Mounting Clips with screws [NATHR-685], and (1) 12" Power Line Interconnector [NARGB-710W].

SPECIFICATION

Construction: The tape can be cut every 6" at marked intervals. Cutting does not effect circuit (shrink wrap tube included for concealment). RGB Tape Light is also separable every 12", each connection has pre-installed shrink wrap around power connections to ensure listing. Simply slice the clear shrink wrap at each electrical connection, and separate pieces. This eliminates soldering when using partial rolls.

Mounting: Each Tape Light includes pre-applied 3M™ adhesive tape for simple installation. Optional channels and clear acrylic clips are available.

Controller: Each run requires a controller or DMX decoder, which can be linked together for color synchronization. The controller can be controlled locally or with an optional hand held remote. DMX decoder requires a DMX controller (by others). Spectrum Wall Slide Control can be used in place of controller or decoder.

Dimming: Dimming RGB tape light is controlled by RGB controller, DMX decoder or Spectrum Wall Slide Control. Dimmable drivers are only for powering tape light runs.

ELECTRICAL

Input Voltage: 12V

Wattage: 2.5W per foot

Color Temperature: Color Changing RGB (up to 16 colors)

Dimming: Dimmable with RGB controller, DMX decoder or Spectrum Wall Slide Control

Maximum Run Length: 24'

LABELS AND LISTINGS

- cULus Listed for Damp Location
- 3-Year Limited Warranty



PRODUCT IMAGES & DIMENSIONS



12V RGB Color Changing LED Tape Light

Length / Tape Light Finish
NUTP6-16LEDRGB = 16' Roll / Amber finish
NUTP6-LEDRGB/12 = 12" Section / Amber finish
NUTP6-LEDRGB/6 = 6" Section / Amber finish

Example: NUTP6-16LEDRGB = 16' 12V RGB Color Changing LED Tape Light Roll, Amber finish

NUTP6 Series

12V RGB Color Changing LED Tape Light Accessories

Type

Project

Catalog No.

Notes



RGB 2.4G Full Color RF Controller and Hand Held Remote

NARGB-860/61

12V/24V controller is required for each RGB LED Tape Light run. Installs between the driver and the power line interconnector. The controller can be used to toggle between colors or changing modes.



RGB Controller and Hand Held Remote (sold separately)

NARGB-760 RGB Controller NARGB-761 RGB Hand Held Remote

360W Max. A controller is required for each RGB LED Tape Light run. Installs between the driver and the power line interconnector. The controller can be used to toggle between colors or changing modes.



DMX Decoder for RGB Tape Light
NATL-DMX-4C

20A Max. A DMX decoder or RGB controller is required for each RGB LED Tape Light run. Installs between the driver and the power line interconnector. The decoder requires a DMX controller (by others) to operate.



Spectrum Wall Slide Control (Controller + Dimmer in One)

NARGB-875W

Dual slide controller and dimmer. One slider controls LED color and other slider controls brightness with a positive off. Installs in wall switch between driver and power line interconnector (NARGB-710W).



Controller Power Line Connector

NARGB-762W 10' Cable NARGB-763W 30' Cable

Replaces included 9-1/2" input wire, to allow for a longer length between RGB controller or DMX decoder and LED driver.



Power Line Interconnector

NARGB-710W 12" Cable


Connects a RGB Tape Light run to a RGB controller or DMX decoder. (1) Power line interconnector is included with every Tape Light roll. Use interconnection cables to increase length.



Interconnection Cables

NARGB-702W 2" Cable NARGB-706W 6" Cable NARGB-718W 18" Cable NARGB-736W 36" Cable NARGB-772W 72" Cable

Allows easy linking of two RGB Tape Lights sections. Cables are flexible and can be moved in any direction, or be joined together for custom lengths.



Splitter Cable

NARGB-700W Y Splitter NARGB-701W X Splitter

Allows splitting the RGB Tape light from a run or driver, into two or three separate runs.




Shrink Wrap Tube / End Cap

NATL-400 Shrink Wrap Tube

Shrink wrap seals connection made in the field. Necessary to maintain cULus listing. Two shrink wrap tubes are included with every Tape Light roll and section.

NATL-403 Black NATL-403W White

Covers open end of tape light




4' Channel / Clear Mounting Clips

NATHR-680 4' Channel / Aluminum

Aluminum channel is field cuttable.

NATHR-685 Clips / Pack of 15


Mounts Tape Light to various surfaces. Pack of 15 clear acrylic mounting clips are included with every Tape Light roll.



4' Shallow Channels

NATL-C23A Aluminum w/Wing NATL-C24A Aluminum NATL-C24B Black NATL-C24W White


Used to mount tape light to various surfaces. Plastic diffuser and end caps included. Field cuttable.



4' Deep Channels

NATL-C25A Aluminum w/Wing NATL-C26A Aluminum NATL-C26B Black NATL-C26W White


Used to mount tape light to various surfaces. Plastic diffuser and end caps included. Field cuttable.



4' J-Style Channels

NATL-C27A Aluminum

Used to mount tape light to various surfaces. Field cuttable.



4' Corner Channels

NATL-C28A Aluminum NATL-C28B Black NATL-C28W White

Plastic diffuser and End caps included. Field cuttable

NUTP6 Series

12V RGB Color Changing LED Tape Light Drivers & Accessories

Type

Project

Catalog No.

Notes



Direct Plug-In LED Driver

NAPK-524W/12 12V 24W

Input Voltage: 120V

Cable Length: 6 Feet



Direct Plug-In LED Driver

NAPK-560W/12 12V 60W

Input Voltage: 120V

Input Wire: 4' Cord and Plug

Output Wire: 4' Power line connector



Class II Hardwire LED Driver

NATL-5060-12-HWD10 12V 60W

Input Voltage: 120-277V

Dimming: N/A for RGB tape

Includes: 10' Power Line Connector



Class II Hardwire LED Driver
with Breakers

NMT-244/12C2D1 4 x 60W

Input Voltage: 120V

Dimming: N/A for RGB tape

Breakers: (4) 60W

NOTE: Power Line Connector(s) not
included



Class II Hardwire LED Driver

NAPKED-5040HW 12V 35W

NAPKED-5060HW 12V 60W

Input Voltage: 120V

Dimming: N/A for RGB tape

Includes: 10' Power Line Connector



Class II Hardwire LED Driver
with Regulator

NMTD-40/12D 12V 40W

NMTD-60/12D 12V 60W

Input Voltage: 120-277V

Dimming: N/A for RGB tape

Regulator: Integral regulator for
constant current and voltage

Includes: 10' Power Line Connector



Power Line Connector

NALTL-10 10' Cable
NALTL-30 30' Cable

For use with Class II drivers. Carries
output from driver, requires power line
interconnectors.



5' Power Line Splitter

NATL-302W

Splits power line connector into two
separate leads, requires power line cable.



2' Wire Raceway

NATL-422B Black
NATL-422W White

Field-cutable plastic. Includes wire channel
with double faced tape and cover.



Low Voltage Splice Box

NATL-415W

Use to join low voltage lead to power
line connector.



Terminal/Splitter Block

NATL-407 4-Way
2-3/8"L x 1-1/8"W x 7/8"D

NATL-408 8-Way
4"L x 1-1/8"W x 7/8"D



16AWG In-Wall Rated Wire

NATL-W16-2-250 16AWG 250'
NATL-W16-2-20 16AWG 20'

16 AWG low voltage Class II two-con-
ductor, in-wall rated wire.



Wire Clip, Plastic - 10pk

NATL-404W J-Clip
NATL-405W Over the Wire
NATL-406W Square Clip