

4PG

Features and Specifications

Applications

Demanding environments that require a water-tight fixture, such as parking garages.

Construction

Durable, lightweight molded white fiberglass body. Hardwire power connection. Polycarbonate latches standard; stainless steel latches available. Ceiling mount brackets included. Other mounting options available upon request.

Certification & Listings

- UL Listed for Wet Locations.
- IP65 and IP67 Certified.
- DesignLights Consortium qualified.
- Visit the DLC QPL for listed models.

Electrical

Available in 120-277v.

Operating Temperature

Thermal cycling temperature rated at -20°F to 113°F [-28.9°C to 45°C].

Optics

Frosted acrylic external lens.

Rated Life

50,000 hours.

Warranty

Orion LED fixtures are covered by a five-year limited warranty. Accessories and individual components are covered by separate OEM supplier warranties.



Required Ordering Information

1 Select	4PG ---
Series	
4PG	4' Parking Garage Enclosed Fixture

2 Select	40W ---
Output	
40W	40 watts

3 Select	LED ---
Technology	
LED	LED

4 Select	---
Power Cord	
[blank]	No whip
6W	6' whip
11W	11' whip

5 Select	--
Integral Sensor	
[blank]	No sensor
WS	Integral Sensor [Wet Rated]

6 Select	--
Color Temperature	
[blank]	5000K [Standard]

Options

SS – Stainless steel latches [Add -SS to the end of the part number]





Physical and Performance Information¹

4PG

Series	Input Voltage	Input Power	Input Current	Power Factor	Light Output ²	CCT	CRI	Width	Length	Height	Weight
4PG	120-277v	47w	0.402-0.174 A	≥.90	4838 lm	5000K	≥80	6.75"	52.0"	4.25"	8.7 lbs.

Additional Specification Information

¹ Actual performance may vary by up to ±10% of values listed

² Average. Actual values will range from 4745K-5310K