

MODEL 8800-CL



WARNING

WARNING — THE INSTALLATION MUST BE CARRIED OUT BY A QUALIFIED ELECTRICIAN.

1. Consult a qualified electrician if you have any questions
2. Disconnect the electrical supply power to the outlet prior to installation
3. For best protection from rain or humidity, be sure to route the cords through the cord knockouts in the cover and press the cover firmly until it snaps closed over the hasp
4. DO NOT use if incorrect cord knockouts are removed

Application Notice

1. This one gang in-use weatherproof enclosure can be used outdoors or in other wet locations (protects receptacles while in use for unattended applications), and be marked "Extra Duty", with the marking being visible after installation
2. NEMA 3R rated and meets National Electrical Code requirements covered by Article 410-57(b) and designed to meet NEC-210-60(b)
3. Complies with new CSA C22.2 NO.42.1 and CEC rule 26-702, as well as NEC section 406.9(b) (1), CEC 2015 26-702

CAUTION

PLEASE READ INSTRUCTION BEFORE COMMENCING INSTALLATION AND RETAIN FOR FUTURE REFERENCES.

Electrical products can cause death or injury, or damage to property.

If in any doubt about the installation or use of this product, consult a competent electrician.

INSTALLATION GUIDE

1. Disconnect power to the receptacle, at the circuit breaker panel before installing
2. If installing on an existing receptacle, remove and discard the existing cover, plate and gasket
3. Position the gasket as required after removing the appropriate perforated sections.
It can be temporarily held onto the back of the base using the mounting hardware provided
4. Mount the base assembly on the receptacle to the junction box using two of long screws provided.
To ensure weatherproof protection, the hinges must be located at the top.
If mounting to an outdoor junction box or FS box, use the remaining long screws to further secure the base assembly to the junction box, using the existing holes. For specially designed junction boxes, mounting holes should be drilled to line up with the hole in the box
5. Be sure all screws are secure but not over-tightened.
Install the remaining short screws into the receptacle as required
6. To open, bend back the polymeric latch while lifting the cover. A hasp is provided for padlocking

WARRANTY

Full One Year Warranty

If within one year from date of purchase this product fails due to a defect in material or workmanship, we will repair or replace it free of charge. This warranty does NOT apply to:

- a) Damage caused by accident, units struck by lightning, abuse, mishandling, dropping
- b) Units which have been subject to unauthorized repair, opened, taken apart
- c) Units not used in accordance with directions
- d) Damages exceeding the cost of the product. Some states do not allow a limitation of damaged so the foregoing limitation may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which may vary from state to state.

ORTECH reserves the right to modify at any time, without notice, any or all of our product's features, designs, components and specifications to meet market changes.