

LED Landscape Lighting — Deck Lights

ORTECH

Instruction Manual

MODEL OD-A2022W

WARNING

WARNING — THE INSTALLATION MUST BE CARRIED OUT BY A QUALIFIED ELECTRICIAN.



1. Read all installation instructions before installing the fixture and keep the attached instruction sheet.
2. This step light is intended for installation in accordance with the National Electric Code (NEC) and local code specifications.
3. The operating voltage range is 9V-15V AC/DC.

Application Notice

TO REDUCE THE RISK OF FIRE, ELECTRIC SHOCK, OR INJURY TO PERSONS, READ THE INSTRUCTIONS BELOW:

1. Keep away from combustibles. Turn OFF / unplug to change lamp. DO NOT touch the lamp and replace after servicing
2. When using multiple luminaires, load is not to exceed the total watts of transformer rating
3. DO NOT operate the LED Deck Light fitted with a missing or damaged shield
4. Install all luminaires 10 feet (3.05m) or more from a pool, spa, or fountain
5. DO NOT touch the lamp directly at any time. Use a soft cloth. Oil from skin may damage the lamp
6. ALWAYS use UL, cUL, and CSA recognized wire connectors for connections
7. DO NOT use extension cords on power units
8. DO NOT touch hot lens, guard, or enclosure

CAUTION


PLEASE READ INSTRUCTION BEFORE COMMENCING INSTALLATION AND RETAIN FOR FUTURE REFERENCES.

Electrical products can cause death or injury, or damage to property.

If in any doubt about the installation or use of this product, consult a competent electrician.

COMPONENTS

Please make sure the following items are included when opening the box:



Fixtures



**Installation
Instruction**



**Mounting
Screws**

INSTALLATION

1. Turn off the power supply.
2. Determine the desired location for each fixture, drill the wireway hole at this time. Hold the fixture in correct direction, lead the wire through the wireway hole, secure with screws.
When installing on surfaces like brick or concrete walls, plastic anchors are required. Mark the location of the holes and drill the holes for the plastic anchors with an appropriate drill bit for the material you are drilling into. Place the plastic anchors in the holes. Drill the wireway hole at this time, lead the wire through the wireway hole, and put fixture to the location, screw the 2 screws into the anchors through the holes on the fixture, securing the fixture.
3. Strip the 2 leads from the fixture pigtail wire. Connect the leads from the fixture to the main low voltage supply cable leads.

