

## FLUSH MOUNTS

1300T-10-3CCT | 1302T-14-3CCT | 1303T-16-3CCT



### HIGHLIGHTS

#### 10", 14" And 16" LED Flush Mounts With Cold Rolled Steel Plate & Rings, With Selectable CCT

- High transmittance & UV protection for outdoor light up
- Ensures uniform lighting without black dots or shadow
- Cover made of a high quality poly methyl metacrylate (PMMA) material
- LED Flush Mount with efficient heat dissipating aluminum pillars

16-36W

120V AC

1120-2520 LMN

80 CRI

### CERTIFICATIONS



### COLOUR TEMPERATURE

3000K / 4000K / 5000K (Selectable)



### SPECIFICATIONS

MODEL	1300T-10-3CCT	1302T-14-3CCT	1303T-16-3CCT
Wattage	16W	26W	36W
Voltage	120V AC, 60Hz	120V AC, 60Hz	120V AC, 60Hz
Lumens	1120 lmn	1820 lmn	2520 lmn
Beam Angle	120°	120°	120°
Lifetime	50,000 hours	50,000 hours	50,000 hours
Dimmable	Yes	Yes	Yes
Grade Of Protection	IP20	IP20	IP20
CRI	80	80	80
Diffuser/Lens Material	PS	PS	PS
Rating	IC rated/Damp location/ Indoor use	IC rated/Damp location/ Indoor use	IC rated/Damp location/ Indoor use
Operating Temperature	-20°C ~ +40°C	-20°C ~ +40°C	-20°C ~ +40°C
Size	Ø10x2.5	Ø14x2.6	Ø16x2.8

**FLAT-OUT  
FABULOUS  
CEILING  
PERFECTION**

**5 YEAR WARRANTY**

### AVAILABLE COLOURS



Satin Nickel

Matte Black

Easy Installation

ORTECH reserves the right to modify at any time, without notice, any or all of our product's features, designs, components and specifications to meet market changes.



## FLUSH MOUNTS

1300T-10-3CCT | 1302T-14-3CCT | 1303T-16-3CCT



REFERENCE	QUANTITY	REMARKS	PROJECT DETAILS
			Project:
			Location:
			Architect:
			Engineer:
			Contractor:
			Submitted By:
			Date:

ORTECH reserves the right to modify at any time, without notice, any or all of our product's features, designs, components and specifications to meet market changes.

