

FLUSH MOUNTS 2400-3CCT



HIGHLIGHTS

16" Adjustable 3 CCT Surface Mount / Semi-flush Mount

- 80 lmn per wattage high efficiency Good quality LGP (Light Guide Plate) and diffuser plate
- Provides uniform lighting with no black dots or shadow









CERTIFICATIONS







COLOUR TEMPERATURE



SPECIFICATIONS

| MODEL | 2400-3CCT | | |
|------------------------|---|--|--|
| Wattage | 30W | | |
| Voltage | 120V AC, 60Hz | | |
| Lumens | 2700 lmn | | |
| Beam Angle | 120° | | |
| Lifetime | 50,000 hours | | |
| Dimmable | Yes | | |
| Grade Of Protection | IP20 | | |
| CRI | 80 | | |
| Diffuser/Lens Material | PS . | | |
| Rating | Non-IC rated/Damp location/ | | |
| | Indoor use | | |
| Operating Temperature | -20°C ~ +40°C | | |
| Application | Corridors / Lobbies / Kitchens / Balconies / Bathrooms / Bedrooms | | |

FLAT-OUT FABULOUS CEILING PERFECTION

5 YEAR WARRANTY

DIMENSIONS



2400-3CCT

A - 15-5/8" (397mm)

B - 14-5/16" (364mm) C - 15-16" (24mm)


ORTECH reserves the right to modify at any time, without notice, any or all of our product's features, designs, components and specifications to meet market changes.





CLOSET LIGHTS





AVAILABLE COLOURS





| REFERENCE | QUANTITY | REMARKS | PROJECT DETAILS | |
|-----------|----------|---------|-----------------|--|
| | | | Project: | |
| | | | Location | |
| | | | Architect: | |
| | | | Engineer: | |
| | | | Contractor: | |
| | | | Submitted By: | |
| | | | Date: | |

ORTECH reserves the right to modify at any time, without notice, any or all of our product's features, designs, components and specifications to meet market changes.