

MICRO COMPACT SERIES

ODD-50-1 ODD-80-1 ODD-100-1

HIGHLIGHTS

Next Generation Single Speed DC Motor Compact Series

- Ultra Silent, High Performance
- Very quiet fan for ceiling or wall mounted Hold
- Comes with a capacitor start motor known for its high efficiency and long lasting reliability



SPECIFICATIONS

Model	ODD-50-1	ODD-80-1	ODD-100-1
Air delivery(CFM at 0.10"S.P.)	50	80	100
Sound Level(Sones)	0.3	0.8	1.0
Fit for bath (sq.ft)	45	75	95
Duct size (inch)	4"		
Motor Power(W)	3.5W	5.5W	8W
Housing dimension (in)	9"x9"x5 3/4"		
Grille dimension (in)	11 7/8"x11 3/8"		
Voltage	120V/60HZ		
Motor	DC motor		
Blower wheel	Centrifugal		
Housing	Galvanized steel		
Grille	plastic		

HOUSING

- Made of rugged 26 GA galvanized steel
- Detachable 4 inch polymeric collar which includes a light weight built-in back draft damper

MOTOR | BLOWER

- DC Motor
- Motor comes with a built-in overload disconnect for safety and longer motor life

TYPICAL SPECIFICATIONS

- Ceiling ventilator shall have corrosion resistance galvanized steel
- It shall be ducted to a roof vent or wall cap using 4 inch round pipe
- Blower assembly shall be removable, have a centrifugal type blower wheel and a permanently lubricated motor designed for continuous operation
- Includes an attachable non-metallic collar with built-in back draft damper



Comes with protective cardboard cover

Warranty is voided if the cardboard is removed anytime during construction.

Reference	QTY.	Remarks	Project:
			Location:
			Architect:
			Engineer:
			Contractor:
			Submitted by:
			Date:

ORTECH reserves the right to modify at any time, without notice, any or all of our product's features, designs, components and specifications to meet market changes.

