

LED Exit Signs

MODEL OE-G026





HIGHLIGHTS

- Has UL-94V-0 flame rating and is fire-retardant
- Includes Test button and charge indicator light
- Provides Overcharge & over-discharge protection
- Injection-molded thermoplastic ABS housing with Universal mounting (wall, side and ceiling)
- LED Edge Lit Running Man Exit Signs with innovative, snap-together design, which allow for fast and easy installation

SPECIFICATIONS

Model	OE-G026
Wattage	Super Bright LED 2W
Voltage	120-347V AC /60Hz
Material	Injection molded thermoplastic ABS housing
Battery	3.6V 300mAh Nickel Cadmium Battery
Emergency Duration Time	≥ 90 min
Conversion Time	< 0.2 seconds
Grade of Protection	IP 20
Insulation	II, Range: 80m ²
Operating Temp.	0°C ~ +40°C

DIMENSIONS



ORTECH reserves the right to modify at any time, without notice, any or all of our product's features, designs, components and specifications to meet market changes.



* Included in packaging

Reference	QTY.	Remarks	Project:
			Location:
			Architect:
			Engineer:
			Contractor:
			Submitted by:
			Date:

ORTECH reserves the right to modify at any time, without notice, any or all of our product's features, designs, components and specifications to meet market changes.