

4" SLIM LIGHTS SLIM-RG4-5CCT



HIGHLIGHTS

4" Regress Downlight Module Changeable Trim With Selectable CCT

- Class 2 transformer in junction box is included No housing required Type IC, air tight & damp
- location rated
 Easy & fast installation install directly into ceiling with
- clips
 Aluminum die-cast construction with beam spread option 38°









CERTIFICATIONS











COLOUR TEMPERATURE

2700K / 3000K / 3500K/ 4000K / 5000K (Selectable)

SPECIFICATIONS

MODEL	SLIM-RG4-5CCT	
Wattage	15W	
Voltage	120V AC, 60Hz	
Lumens	1000 lmn	
Beam Angle	380	
Lifetime	50,000 hours	
Dimmable	Yes (TRIAC dimming)	
CRI	80Ra	
Rating	IC rated/Indoor use/	
	Damp Location	
Grade of Protection	IP44	
Cutout	Ø3-3/4" (95mm)	
Operating Temperature	-20°C ~ +40°C	
Case Quantities	18	

ELEVATE YOUR LIGHTING **GAME**

5 YEAR WARRANTY

DIMENSIONS Ø4-1/2" (115mm)

ORTECH reserves the right to modify at any time, without notice, any or all of our product's features, designs, components and specifications to meet market changes.




4" SLIM LIGHTS

INCLUDED IN BOX

• 4" Regress Downlight with Remote Driver







INTERCHANGEABLE REFLECTORS (SOLD SEPARATELY)



SLIM-RG4-RF-ALCH ALZEK CHROME



SLIM-RG4-RF-ALHZ ALZEK HAZE



SLIM-RG4-RF-BFWH WHITE BAFFLE



SI IM-DG4-DF-RERK

INTERCHANGEABLE RINGS (SOLD SEPARATELY)







SLIM-RG4-RING-BK SLIM-RG4-RING-SN SLIM-RG4-RING-WH REGULAR BLACK RING REGULAR SATIN NICKEL RING REGULAR WHITE RING

ACCESSORIES (SOLD SEPARATELY)



CORD-24 | 60 | 120 | 240



PLATE13-3A | PLATE13-3A-L | PLATE26-3A | PLATE26-3A-L Construction plate made up of galvanized steel for recessed lighting



PLATE3A-HB Galvanized steel mounting plate with hanger bars



OT-010-RG4 0-10V Class 2 LED Drive

REFERENCE	QUANTITY	REMARKS	PROJECT DETAILS	
			Project:	
			Location	
			Architect:	
			Engineer:	
			Contractor:	
			Submitted By:	
			Date:	

ORTECH reserves the right to modify at any time, without notice, any or all of our product's features, designs, components and specifications to meet market changes.